

The sleek, sporty Colt Twin scooter delivers unique dual front wheels the maximum stability of a four-wheel scooter. The Colt Twin has a full complement of advanced standard features such as low-profile tyres and a wraparound delta tiller.





## **Specifications**

Weight Capacity	25 st (159 kg)
Maximum Speed <sup>1</sup>	Up to 4 mph
Ground Clearance <sup>3</sup>	57 mm (2.25")
Turning Radius³	1067 mm (42")
Overall Length <sup>3</sup>	1160 mm (46")
Overall Width <sup>3</sup>	560 mm (22")
Max. Obstacle Climb	50mm (2")
Drive Tyres	230 mm front - solid 250 mm rear - solid
Suspension	-
Total Weight Without Batteries <sup>3, 4</sup>	62.5 kg (138 lbs)
Heaviest Piece When Disassembled <sup>3</sup>	Front section: 27.3 kg (60 lbs)
Drivetrain	24 volt DC motor
Dual Breaking System	Regenerative & electromechanical
Battery Requirements <sup>3</sup>	2 x 35 Ah deep cycle
Battery Weight <sup>4</sup>	10.43 kg (23lbs) each
Battery Charger	Off-board
Colour	Red & blue



## **Features**

- Comfortable high back seat with armrests
- High visability front and rear LED lighting
- Wrap around delta tiller
- Large storage pocket in seat
- Large amount of leg room
- Exclusive & stylish low profile tyres
- Convienient fron basket

## Available in:

- Red
- Blue





NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (+ or -) 10%

be subject to a variance of (+ or -) 10%.
2 Includes standard seat weight.

<sup>3</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

this specification can be subject to a variance of (+ or -) 3%.

4 Battery weight may vary based on battery manufacturer.