

## Product Information Sheet

| #         | INFORMATION  |                            | Value and precision                                    | Unit            |
|-----------|--|----------------------------|--|-----------------|
| 1         | Supplier's name or trade mark  |                            | Pixio  |                 |
| 2         | Supplier's model identifier  |                            | PX274P   |                 |
| 3         | Energy efficiency class for standard Dynamic Range (SDR)   |                            | F  |                 |
| 4         | On mode power demand for Standard Dynamic Range (SDR)  |                            | 25.00  | W               |
| 5         | Energy efficiency class (HDR)  |                            | /  |                 |
| 6         | On mode power demand in High Dynamic Range (HDR) mode  |                            | /  | W               |
| 7         | Off mode, power demand   |                            | 0.20   | W               |
| 8         | Standby mode power demand  |                            | 0.27   | W               |
| 9         | Networked standby mode power demand  |                            | n.a.   | W               |
| 10        | Electronic display category  |                            | Monitor  |                 |
| 11        | Size ratio   |                            | 16:9   | integer         |
| 12        | Screen resolution (pixels)   |                            | 2560x1440  | pixels          |
| 13        | Screen diagonal  |                            | 69.00  | cm              |
| 14        | Screen diagonal  |                            | 27   | inches          |
| 15        | Visible screen area  |                            | 20.08  | dm <sup>2</sup> |
| 16        | Panel technology used  |                            | LED  |                 |
| 17        | Automatic Brightness Control (ABC) available   |                            | NO   | [YES/NO]        |
| 18        | Voice recognition sensor available   |                            | NO   | [YES/NO]        |
| 19        | Room presence sensor available   |                            | NO   | [YES/NO]        |
| 20        | Image refresh frequency rate   |                            | 75   | Hz              |
| 21        | Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market) |                            | 3  | years           |
| 22        | Minimum guaranteed availability of spare parts (from the date of end of the placement on the market)                   |                            | 2  | years           |
| 23        | Minimum guaranteed product support   |                            | 3  | years           |
|           | Minimum duration of the general guarantee offered by the supplier  |                            | 3  | years           |
| 24        | Power supply type:   |                            | External   |                 |
| <i>i</i>  | External standardised power supply (included in the product box)   | Standard name              | SHENZHEN FUJIA APPLIANCE CO., LTD.<br>FJ-SW20171204500 |                 |
|           |  | Input voltage              | AC 100 -240  | V               |
|           |  | Output voltage             | 12.00  | V               |
| <i>ii</i> | External standardised suitable power supply (if not included in the product box)                                       | Standard name              | n.a.   |                 |
|           |  | Required output voltage    | n.a.   | V               |
|           |  | Required delivered current | n.a.   | A               |
|           |  | Required current frequency | n.a.   | Hz              |