



LNB

KU-BAND PLL COMPACT

1000H



SPECIFICATIONS

Noise Figure	0.7 - 0.9 dB typ. at room temp. @ CF (0.8 - 1.0 dB max.)
L.O. Stability	± 10 kHz to ± 25 kHz (Depending on model number)
Phase Noise (SSB) max.	-75 dBc/Hz at 1 kHz -80 dBc/Hz at 10 kHz -95 dBc/Hz at 100 kHz
Input VSWR	2.5 : 1 max.
Output VSWR	2.2 : 1 max.
Gain	60 dB typ., 55 dB min., 65 dB max.
Gain Flatness (over full band)	≤ 4 dB p-p
Output P1dB	+ 5 dBm min.

DC Power	+ 15 to + 24 V DC
Current drain	300 mA max.
Input (waterproof)	WR-75 waveguide grooved
Output (waterproof)	F-Connector (75 Ohm) N-Connector (50 Ohm)
Dimensions (L x W x H)	110 mm x 42 mm x 42 mm (4.3 in x 1.7 in x 1.7 in)
Weight	300 g (10.58 oz)
Operating Temperature	- 40 to + 60°C
Storage Temperature	- 40 to + 80°C


Note: See HS1000 for <5 kHz L.O. stability

FREQUENCY BANDS

	1000HA	1000HB	1000HC
Frequency Band (GHz)	11.70 - 12.20	12.25 - 12.75	10.95 - 11.70
L.O. Frequency (GHz)	10.75	11.30	10.00
IF Frequency (MHz)	950 - 1450	950 - 1450	950 - 1700

HOW TO ORDER

1208HAF



MECHANICAL DIAGRAM

