


Qty.	Description
1	<p data-bbox="204 338 448 365">GT-C-130 PN8.6 G1 V</p> <div data-bbox="352 383 437 629" style="text-align: center;">  </div> <p data-bbox="204 658 464 685">Product No.: 96733306</p> <p data-bbox="204 719 1482 819">Liquid max temp: Grundfos GT-C-130 PN8.6 G1 V is a Diaphragm pressure tank, with a capacity of 130.0 l and Vertical installation. The tanks are approved for drinking water. The GT-C-130 PN8.6 G1 V is designed for a maximum operation pressure of 8.6 bar and a maximum liquid temperature of 50 °C.</p> <p data-bbox="204 981 1482 1032">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1039 1482 1122">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="204 1155 1482 1238">Product name: The tank is a lightweight composite pressure tank. The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1272 1482 1323">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1330 1482 1413">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="204 1447 1482 1565">The tanks have a non-replaceable diaphragm that is pre-charged with nitrogen (1.5 bar). The tanks have a non-toxic butyl rubber diaphragm, dividing the tank chamber into two compartments. The upper compartment contains compressed nitrogen. The lower compartment has a liner of polypropylene (PP) and is filled with water from the pump.</p> <p data-bbox="204 1599 1482 1727">A pressure tank ensures controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss. The result is increased comfort in your installation by limiting the start/stop frequency of your pump, and it increases system comfort by compensating for pressure drops when a tap is opened, while reducing problems with water hammer in the pipework.</p> <p data-bbox="204 1800 628 1854">Liquid: Maximum liquid temperature: 50 °C</p> <p data-bbox="204 1888 687 1942">Technical: Membrane type: Diaphragm</p> <p data-bbox="204 1975 683 2029">Materials: Basic: Composite</p> <p data-bbox="204 2063 328 2089">Installation:</p>



Company name:

Created by:

Phone:

Date:

15/04/2021

Qty.	Description
	<p>Maximum operating pressure: 8.6 bar Type of connection: G Size of connection: 1 inch Size: 130.0</p> <p>Others: Net weight: 12.8 kg Gross weight: 15.4 kg Applicat. typ: Standard Finnish LVI No.: 3413402 Norwegian NRF no.: 9100154</p>

Description	Value
General information:	
Product name:	GT-C-130 PN8.6 G1 V
Product No:	96733306
EAN number:	5700838022285
Price:	
Technical:	
Membrane type:	Diaphragm
Materials:	
Basic:	Composite
Installation:	
Maximum operating pressure:	8.6 bar
Pre-pressure:	1.4 bar
Type of connection:	G
Size of connection:	1 inch
Installation:	Vertical
Size:	130.0
Liquid:	
Maximum liquid temperature:	50 °C
Others:	
Net weight:	12.8 kg
Gross weight:	15.4 kg
Applicat. typ:	Standard
Finnish LVI No.:	3413402
Norwegian NRF no.:	9100154

