

Qty.	Description																
1	<p data-bbox="199 338 534 367">Rigid suction lance w/o level</p> <p data-bbox="199 367 467 396">Product No.: 98071015</p> <p data-bbox="199 396 892 427">Rigid suction lance with adjustable length for mounting in a tank.</p> <p data-bbox="199 427 1425 481">They are installed at the lower end of the suction hose and consist of strainer (mesh size 0,8mm) non return valve, protective pipe and tank connection with entry holes for relief line and deaeration line</p> <p data-bbox="199 546 316 573">Technical:</p> <table data-bbox="199 573 627 633"><tr><td data-bbox="199 573 319 602">Max. Flow:</td><td data-bbox="564 573 627 602">60 l/h</td></tr><tr><td data-bbox="199 602 395 633">Pump connection:</td><td data-bbox="564 602 627 633">G5/8</td></tr></table> <p data-bbox="199 665 309 692">Materials:</p> <table data-bbox="199 692 659 781"><tr><td data-bbox="199 692 268 721">Basic:</td><td data-bbox="564 692 600 721">PE</td></tr><tr><td data-bbox="199 721 316 750">Valve ball:</td><td data-bbox="564 721 659 750">Ceramic</td></tr><tr><td data-bbox="199 750 284 781">Gasket:</td><td data-bbox="564 750 627 781">PTFE</td></tr></table> <p data-bbox="199 813 325 840">Installation:</p> <table data-bbox="199 840 767 929"><tr><td data-bbox="199 840 416 871">Type of connection:</td><td data-bbox="564 840 627 871">Hose</td></tr><tr><td data-bbox="199 871 432 902">Pipework connection:</td><td data-bbox="564 871 767 902">4/6, 6/9, 6/12, 9/12</td></tr><tr><td data-bbox="199 902 440 934">Max immersion depth:</td><td data-bbox="564 902 655 934">690 mm</td></tr></table>	Max. Flow:	60 l/h	Pump connection:	G5/8	Basic:	PE	Valve ball:	Ceramic	Gasket:	PTFE	Type of connection:	Hose	Pipework connection:	4/6, 6/9, 6/12, 9/12	Max immersion depth:	690 mm
Max. Flow:	60 l/h																
Pump connection:	G5/8																
Basic:	PE																
Valve ball:	Ceramic																
Gasket:	PTFE																
Type of connection:	Hose																
Pipework connection:	4/6, 6/9, 6/12, 9/12																
Max immersion depth:	690 mm																



Company name:

Created by:

Phone:

Date:

27/05/2021

Description	Value
General information:	
Product name:	Rigid suction lance w/o level
Product No:	98071015
EAN number:	5710628438431
Price:	
Technical:	
Max. Flow:	60 l/h
Pump connection:	G5/8
Materials:	
Basic:	PE
Valve ball:	Ceramic
Gasket:	PTFE
Installation:	
Type of connection:	Hose
Pipework connection:	4/6, 6/9, 6/12, 9/12
Max immersion depth:	690 mm