

Qty.	Description																
1	<p data-bbox="204 338 533 367"><b>Rigid suction lance w/o level</b></p> <p data-bbox="204 367 464 396">Product No.: <a href="#">98071051</a></p> <p data-bbox="204 396 890 425">Rigid suction lance with adjustable length for mounting in a tank.</p> <p data-bbox="204 425 1422 481">They are installed at the lower end of the suction hose and consist of strainer (mesh size 0,8mm) non return valve, protective pipe and tank connection with entry holes for relief line and deaeration line</p> <p data-bbox="204 546 316 575">Technical:</p> <table data-bbox="204 575 628 633"><tr><td data-bbox="204 575 320 604">Max. Flow:</td><td data-bbox="564 575 628 604">60 l/h</td></tr><tr><td data-bbox="204 604 395 633">Pump connection:</td><td data-bbox="564 604 628 633">G5/8</td></tr></table> <p data-bbox="204 665 309 694">Materials:</p> <table data-bbox="204 694 659 781"><tr><td data-bbox="204 694 268 723">Basic:</td><td data-bbox="564 694 596 723">PE</td></tr><tr><td data-bbox="204 723 316 752">Valve ball:</td><td data-bbox="564 723 659 752">Ceramic</td></tr><tr><td data-bbox="204 752 284 781">Gasket:</td><td data-bbox="564 752 628 781">PTFE</td></tr></table> <p data-bbox="204 813 325 842">Installation:</p> <table data-bbox="204 842 767 929"><tr><td data-bbox="204 842 416 871">Type of connection:</td><td data-bbox="564 842 628 871">Hose</td></tr><tr><td data-bbox="204 871 432 900">Pipework connection:</td><td data-bbox="564 871 767 900">4/6, 6/9, 6/12, 9/12</td></tr><tr><td data-bbox="204 900 440 929">Max immersion depth:</td><td data-bbox="564 900 668 929">1100 mm</td></tr></table>	Max. Flow:	60 l/h	Pump connection:	G5/8	Basic:	PE	Valve ball:	Ceramic	Gasket:	PTFE	Type of connection:	Hose	Pipework connection:	4/6, 6/9, 6/12, 9/12	Max immersion depth:	1100 mm
Max. Flow:	60 l/h																
Pump connection:	G5/8																
Basic:	PE																
Valve ball:	Ceramic																
Gasket:	PTFE																
Type of connection:	Hose																
Pipework connection:	4/6, 6/9, 6/12, 9/12																
Max immersion depth:	1100 mm																



Company name:

Created by:

Phone:

Date: 27/05/2021

Description	Value
<b>General information:</b>	
Product name:	Rigid suction lance w/o level
Product No:	<a href="#">98071051</a>
EAN number:	5710628438790
Price:	
<b>Technical:</b>	
Max. Flow:	60 l/h
Pump connection:	G5/8
<b>Materials:</b>	
Basic:	PE
Valve ball:	Ceramic
Gasket:	PTFE
<b>Installation:</b>	
Type of connection:	Hose
Pipework connection:	4/6, 6/9, 6/12, 9/12
Max immersion depth:	1100 mm