



AQUACORP

MODEL: AQBWRO-16

Features

- ▶ Permeate Flow Meter (5 To 40 LPM)
- ▶ Concentrate Flow Meter (5 to 40 LPM)
- ▶ Recycle Flow Meter (5 to 40 LPM)
- ▶ Feed Pressure Gauge (0 to 1.5 MPa)
- ▶ RO Pressure Gauge (0 to 3.5 MPa)
- ▶ 2nd Stage Pressure Gauge (0 to 3.5 MPa)
- ▶ 3rd Stage Pressure Gauge (0 to 3.5 MPa)
- ▶ Concentrate Pressure Gauge (0 to 3.5 MPa)
- ▶ Recovery Pressure Gauge (0 to 3.5 MPa)
- ▶ 20" 5-Rd Cluster 5 & 1 Micron Sediment Pre-filters
- ▶ Low Feed Inlet Pressure Switch
- ▶ Inlet Solenoid Valve 220v 50Hz
- ▶ Flush Solenoid Valve 220v 50Hz
- ▶ ROC 2315 Microprocessor Controller with Temperature & Conductivity Monitor (0-2000 μ s/cm) & Adjustable Flush Time Sequencing
- ▶ RO Light (on ROC 2315 control)
- ▶ RO Pump Indicator Light (on ROC 2315 control)
- ▶ Low Feed Pressure Indicator Light (on ROC 2315)
- ▶ Tank Full Indicator Light (on ROC 2315 control)
- ▶ Auto Flush Indicator Light (on ROC 2315 control)
- ▶ High Pressure Pump Discharge Valve
- ▶ Recycle S/S Needle Valve
- ▶ Concentrate S/S Needle Valve
- ▶ Check Valve in Recycle Line
- ▶ Emergency Stop Switch w/- Indicator Light
- ▶ Power On/Off & Reset Switch w/- Indicator Light
- ▶ RO Pump On/Off Switch w/- Indicator Light
- ▶ Manual Flush On/Off Switch w/- Indicator Light
- ▶ Delay Timer 0-180 sec.



Photo for illustration purposes only and may not represent actual model.

REVERSE OSMOSIS MACHINE

Specifications

RO System	▶ Brackish Water
Model	▶ AQBWRO-16
Performance	▶ at 25°C, 2000ppm TDS
Permeate Rate	▶ 725 LPH Nominal at a recommended operating flux of 23 l/mh
Recovery Rate	▶ 945 LPH Maximum at a maximum operating flux of 30 l/mh
Operating Pressure	▶ 50 to 75% Depending on Raw Water Feed Quality & Water Temperature
Inlet Water Pressure	▶ 900kpa – 1200kpa (130-170psi)
Typical Ion Rejection	▶ 280kpa minimum – 500kpa maximum
Membrane Housing	▶ 95% to 98%
Membrane	▶ 4 x 4"x40" 300psi Fiberglass Housing End Entry
Membrane Model	▶ 4 x 4"x40" Brackish
Array	▶ Hydranautics – CPA5 LD 4040
Pump	▶ 2-1-1 (1 Element per Housing)
Motor	▶ Multi-Stage Centrifugal 304 Stainless Steel Flanged Pump Model CDLF2-22
High Pressure Piping	▶ 2.2KW, 415 VAC/50Hz Three Phase
Electrical Panel	▶ Sch 80 PVC Imperial Pipe Work
Frame	▶ Australian Approved Electrical Box
Pre-treatment Filter	▶ Quality Stainless Steel
Connections	▶ 2 x PVC 5-Round 20" Cartridge Housings
Dimension	▶ 1½" F.I. Inlet, ¾" F.I. Permeate, ¾" F.I. Concentrate
Approximate Weight	▶ 167cm H x 180cm W x 110cm D
	▶ 170kg

Note:- Performance will vary depending on raw water quality and temperature.

The importer reserves the right to change specification / performance without notice and without incurring any obligation related to such changes.