




Check valve type 561 PVC-U
With solvent cement sockets Inch ASTM
Inclusive 2 threaded valve ends NPT

Model:

- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360
- New DN65-DN100



d (mm)	DN (mm)	Thread Type	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)
16	10	NPT	3/8	16	190	161 561 101	1	0.130
20	15	NPT	1/2	16	180	161 561 102	1	0.161
25	20	NPT	3/4	16	380	161 561 103	1	0.184
32	25	NPT	1	16	460	161 561 104	1	0.372
40	32	NPT	1 1/4	16	850	161 561 105	1	0.510
50	40	NPT	1 1/2	16	1080	161 561 106	1	0.720
63	50	NPT	2	16	1670	161 561 107	1	1.327
75	65	NPT	2 1/2	16	2950	161 561 108	1	3.230
90	80	NPT	3	16	3600	161 561 109	1	5.080
110	100	NPT	4	16	4150	161 561 110	1	8.150

FKM Code	SP	Weight (kg)	D (mm)	L (mm)	L2 (mm)	z (mm)
161 561 111	1	0.130	50	105	56	67
161 561 112	1	0.130	50	105	56	61
161 561 113	1	0.280	58	121	65	70
161 561 114	1	0.300	68	133	71	76
161 561 115	1	0.510	84	154	85	90
161 561 116	1	0.760	97	164	89	94
161 561 117	1	1.330	124	183	101	107
161 561 118	1	3.250	166	233	136	144
161 561 119	1	5.100	200	254	141	151
161 561 120	1	8.190	238	301	164	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>