PRODUCT DATA SHEET

Purolite[®] C100E

Polystyrenic Gel, Strong Acid Cation Resin, Sodium form, Potable Water Grade

PRINCIPAL APPLICATIONS

- Softening Potable Water
- Food and beverage processing
- Softening Industrial

ADVANTAGES

- Efficient regeneration
- Good kinetic performance
- Low extractables

REGULATORY APPROVALS

- Compliant with FDA Regulation 21 CFR 173.25 for Food Treatment, Ion Exchangers
- Kosher Certified
- Certified by the WQA to NSF/ANSI-61 Standard

TYPICAL PACKAGING


- 1 ft³ Sack
- 25 L Sack
- 5 ft³ Drum (Fiber)
- 1 m³ Supersack
- 42 ft³ Supersack


TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Gel polystyrene crosslinked with divinylbenzene		
Appearance	Spherical Beads		
Functional Group	Sulfonic Acid		
Ionic Form	Na ⁺ form		
Total Capacity (min.)	1.9 eq/L (41.5 Kgr/ft³) (Na ⁺ form)		
Moisture Retention	46 - 50 % (Na ⁺ form)		
Particle Size Range	300 - 1200 μm		
< 300 µm (max.)	1 %		
Uniformity Coefficient (max.)	1.7		
Reversible Swelling, $Na^+ \rightarrow H^+$ (max.)	10 %		
Reversible Swelling, $Ca^{2+} \rightarrow Na^+$ (max.)	8 %		
Specific Gravity	1.27		
Shipping Weight (approx.)	800 - 840 g/L (50.0 - 52.5 lb/ft³)		
Temperature Limit	120 °C (248.0 °F)		



Hydraulic Characteristics









Australia	Indonesia		
	Indonosia	Morocco	Taiwan
Bahrain	Israel	New Zealand	Tunisia
Brazil	Italy	Poland	Turkey
Canada	Japan	Romania	UK
China	Jordan	Russia	Ukraine
Czech Republic	Kazakhstan	Singapore	USA
France	Korea	Slovak Republic	Uzbekistan
Germany	Malaysia	South Africa	



Americas

Purolite 2201 Renaissance Blvd. King of Prussia, PA 19406 T +1 800 343 1500 T +1 610 668 9090 F +1 800 260 1065 americas@purolite.com

EMEA

Purolite Ltd. Unit D Llantrisant Business Park Llantrisant, Wales, UK CF72 8LF T +44 1443 229334 F +44 1443 227073 emea@purolite.com

FSU Purolite Ltd. Office 6-1 36 Lyusinovskaya Str. Moscow, Russia 115093 T +7 495 363 5056 F +7 495 564 8121 fsu@purolite.com

Asia Pacific

Purolite China Co. Ltd. Room 707, C Section Huanglong Century Plaza No.3 Hangda Road Hangzhou, Zhejiang, China 310007 T +86 571 876 31382 F +86 571 876 31385 asiapacific@purolite.com

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.



2023 Purolite All rights reserved. www.purolite.com