Laser 8:1 Downhaul Rigging Guide


southeastsailboats.co.uk

Thank you for purchasing from SoutheastSailboats / ropesforboats. Hopefully these rigging instructions are self explanatory. If you have any problems please contact us at sales@southeastsailboats.co.uk or sales@ropesforboats.co.uk or sales@ropesforboats.co.uk or sales@ropesforboats.co.uk or sales@ropesforboats.co.uk or sales@southeastsailboats.co.uk or sales@ropesforboats.co.uk or sales@southeastsailboats.co.uk or <a href=

The system comprises two parts:

- Part 1 Primary line with two Harken 29mm T2 blocks
- Part 2 Lower block assembly with Harken 29mm T2 block, strop and secondary control line

This version attaches the primary to a caribiner at the top of the kicker assembly.




Step by Step Rigging Instructions:

Step 1 – Start by passing the loop on the end of the primary (Part 1) through the sail cringle.

Step 2 – Pull the loop on the end of the primary line down to the level of the kicker and attach to the caribiner or directly to the tope of the kicker assembly



Step 3 – Pass the lower block assembly strop around the mast under the kicker tang



Step 4 – Thread the end of the secondary control line and the block through the loop on the lower block assembly strop.



Step 5 – Route the secondary control line through the three blocks – it should look like the photos below.





