# Evolution<sup>®</sup> 5600 Thermal Imaging Camera

Product Information






Because every life has a purpose...

The Evolution 5600 TIC delivers reliable thermal imaging performance in a value-driven design for firefighters everywhere. Versatile TIC provides detailed images from the vanadium oxide microbolometer sensor and features 120X120 focal plane array with more than 15, 000 pixels and 39° field of view.


MSA's highly functional Heat Seeker and Quick Temp functions are standard and deliver unmatched performance and superior image quality at all temperatures. As with all MSA TICs, the Evolution 5600 TIC offers standard two-year camera core warranty and one-year warranty on all other camera components. The Evolution 5600 TIC incorporates userfriendly form factors in MSA's 5000 Series TICs:

- Single-button activation
- · Patented dual-handle design for ease of handoff
- · Lightweight lithium-ion battery with more than two hours of run time
- Protective battery compartment
- Comprehensive choice of interchangeable accessories

| Features                  | Benefits  |
|---------------------------|---|
| Heat Seeker Plus          | Only MSA offers color pixelization in<br>high- and low-sense modes    |
| Quick Temp                | Numerical temperature scene readout                                   |
| Instant power-on          | Camera starts in 2 seconds or less                                    |
| 120X120 focal plane array | High-performance VOx infrared sensor                                  |
| High-sense imagery        | Best high-sense imagery; 2 to 4 times longer than competitive cameras |



High Sense image detail with Heat Seeker enhances heat source with red isotherm



Low Sense image detail with Heat Seeker enhances heat source with red isotherm

# Specifications

| DETECTOR             | Uncooled microbolometer vanadium oxide (VOx)                 |
|----------------------|--|
| ARRAY FORMAT         | 120X120  |
| PIXEL SIZE           | 38 μm  |
| SPECTRAL<br>RESPONSE | 7.5 to 13.5 μm   |
| VIDEO OUTPUT         | NTSC   |
| FRAME RATE           | 40mK (nominal)   |
| NEdT                 | ≤ 85mK (in High Sensitivity)<br><=300mK (in Low Sensitivity) |
| TIME TO IMAGE        | < 2 seconds  |
| SCENE TEMP<br>RANGE  | 560°C (1040°F)   |
| WEIGHT               | 48.2 oz (with battery)                                       |
| DIMENSIONS           | 10.8" x 8.1" x 4.4" (HxWxD)                                  |
| VIDEO OUTPUT         | RS-170   |
| OPERATING TIME       | > 2 hours  |

# Ordering Information

| Evolution 5600 TIC complete   | Fahre |
|-------------------------------|-------|
| with Heat Seeker, Quick Temp  | 1009  |
| and User's instruction manual |       |

| Part Number |          |  |
|-------------|----------|--|
| ahrenheit   | Celsius  |  |
| 10097331    | 10097332 |  |



# Thermal Imaging Camera Kits

#### **Fire Station TIC Kit** P/N 10096887

Contains all components and accessories needed to put Evolution TIC into service.

- Two rechargeable lithium-ion batteries
- Single-unit AC charger
- Retractable lanyard
- Carabiner
- Instructional CD
- Hard plastic carrying case



## **Vehicle TIC Kit** P/N 10096886

Contains all components and accessories needed for Evolution TIC fire truck installation.

- Two rechargeable lithium-ion batteries
- Universal Truck Charger
- Retractable lanyard
- Carabiner
- Instructional CD



# Video Transmission and Recording Systems

#### **Mini Receiver Kit** P/N 10050375

Provides customization of video monitoring and recording setup.

- Two-channel receiver
- Multiple power cords
- Additional adapters packaged in soft-sided case
- Additional room for accessories and transmitter
- Magnetic-mounted, omnidirectional antenna standard

#### **Evolution Video Transmitter** P/N 10047573

Self-contained, modular design for maximum flexibility of transmitter deployment.

- Requires no TIC modification
- Independent power supply does not draw power from TIC battery, allows for maximum run time of both TIC and transmission system.



## **Deluxe Receiver Kit** P/N 10050375

Provides complete solutions for viewing transmitted images using single receiver console.

- 12" display integrated into protective Pelican case lid
- Omni-directional antenna, wall-type and cigarettelighter powered supply cords that can use 110-220 volt AC, 12 volt or DC current







## **Evolution Video Capture Kit** P/N 10071750

Small, easy-to-use, stand-alone video device records screen action of any Evolution 5000 Series TIC for up to 2 hours.

- Connects in seconds
- Provides downloadable fireground video clips for recordkeeping and training





# Accessories

#### Single-unit Charger P/N 10041100

- Desktop charger for Evolution TIC lithium-ion batteries
- Requires 110 or 22 volt AC power supply



#### Non-charging Universal Truck Bracket P/N 10067707

- Bracket secures Evolution TIC within vehicle
- System does not have charging capabilities



#### Universal Truck Charger P/N 10067565

- Charges any Evolution 5000 Series TIC with or without wireless transmitter or video capture unit attached
- Smart universal charger trickle charges battery inside TIC first, then switches to spare battery charging module



## Reflective Label ID Kit P/N 10062184

Highly reflective write-on labels enable easier TIC accountability, providing additional reflectivity on Evolution 5000 Series top and sides.

- Each kit contains 5 sets of 4 labels in bright red, orange, yellow, green, and blue
- Labels are easily written using permanent marker



| Description               | P/N      | Description           | P/N      |
|---------------------------|----------|-----------------------|----------|
| Sun shroud                | 10039603 | Plastic carrying case | 10040223 |
| Disposable display covers | 10038970 | Retractable lanyard   | 10040226 |
| Lithium-ion battery       | 10038412 | Shoulder strap        | 10039515 |
| Tripod adapter            | 10040229 | Wrist strap           | 10039516 |
| Carabiner                 | 10040005 |                       |          |

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood.

Only they contain the complete and detailed information concerning proper use and care of these products.



ID 3400-100-MC / November 2012 © MSA 2012 Printed in U.S.A.

#### MSA Corporate Center

1000 Cranberry Woods Drive Cranberry Township, PA 16066 USA Phone 724-776-8600 www.MSAsafety.com U.S. Customer Service Center

Phone 1-800-MSA-2222 Fax 1-800-967-0398



 MSA Mexico

 Phone
 01 800 672 7222

 Fax
 52 - 44 2227 3943

 MSA Interrutional

 Phone
 724-776-8626

 Toll Free
 1-800-672-7777

 Fax
 724-741-1559

 Toll Free
 1-800-672-7777

 Fax
 724-741-1559

 Email
 msa.international@msasafety.com

## Offices and representatives worldwide

For further information:

