

**FORCE2™ WEBBING LANYARDS  
SINGLE TAIL**

# THE NEXT REVOLUTION IN LANYARD TECHNOLOGY



**THE NEW AND IMPROVED FORCE2™  
SHOCK ABSORBING LANYARD RANGE**

**LIGHTEST, STRONGEST, SMALLEST SHOCK  
ABSORBER IN THE WORLD**



Contact Capital Safety for more information on DBI-SALA's range of new FORCE2™ Shock Absorbing Lanyards or visit [www.FORCE2.capitalsafety.com.au](http://www.FORCE2.capitalsafety.com.au). Alternatively scan the QR Code with your smart phone/tablet using a QR scanner/reader. (QR readers are available for free from your device's app store.)



THE ULTIMATE IN FALL PROTECTION

PRODUCT SHEET

# FORCE2™ WEBBING LANYARDS SINGLE TAIL

## ELIMINATING THE SHOCK FACTOR FOR SAFE & SECURE CONNECTIONS

Ideal for Fall Arrest, Work Positioning and Restraint

DBI-SALA shock absorbing lanyards combine strength and ease of use providing a safe and secure means of connecting your fall protection harness to a secure anchorage point. They are designed to quickly and effectively arrest a fall, whilst minimising shock loads on the body.

### FORCE2™ WEBBING SHOCK ABSORBING LANYARDS - SINGLE TAIL

Z10200909



Z10200909E



Z11200909



Z11204545



Z11206161



#### FEATURES

- Lightest, strongest and smallest shock absorber in the world, 66% smaller and 40% lighter
- Minimises shock loads on the body limiting the arresting forces to under 6kN in the event of a fall
- Shock absorber includes Hi-10™ Energy Management Material protected by a rugged and durable soft cover
- Lanyard and shock pack stitching visible for easy inspection
- REPEL™ technology webbing, repels liquids, naturally self-cleaning and enhances durability
- Fully compatible hardware to remove the risk of accidental disengagement from forced roll-out
- 16kN gate strength on all hooks/karabiners, removes the risk of accidental disengagement from excessive gate loadings
- Hi-Vis yellow webbing for easy identification and added visual safety
- Non-grinning webbing on elasticated models for increased durability
- Protected labels for durability and longevity
- Rated to 160kg - ideal for all workers regardless of shape, size and weight
- i-Safe™ enabled to track inspections, control inventory and manage information
- Ideal for use in all kinds of industrial environments and applications

Indicates the product utilises triple action hooks and/or karabiners making them ideal for use in mining applications

NOTE: Twin tail models also available, refer to separate product sheet.

#### Specifications:

Part Number	Connectors		Length	Weight (Approx.)	Tails	Flat Webbing	Elasticated Webbing	Adjustable
	Harness	Anchorage						
Z10200909	9502116	9502116	2m	1.00kg	Single	✓		
Z10200909E	9502116	9502116	2m	1.10kg	Single		✓	
Z11200909	9502116	9502116	750mm - 2m	1.15kg	Single	✓		✓
Z11204545	R-119	R-119	750mm - 2m	1.05kg	Single	✓		✓
Z11206161	8700552	8700552	750mm - 2m	0.85kg	Single	✓		✓

**Webbing:** REPEL™ technology webbing - 45mm. **Thread:** Polyester. **Adjuster:** Fall arrest rated drop forged steel, 22kN. **LPD:** Polycarbonate (design patent pending). **Hooks & Karabiners:** Refer to separate product information sheets. **Capacity:** 50-160kg (combined weight of person, tools, clothing, etc.). **Minimum Breaking Strength:** 15kN. **Activation:** Activates at a minimum force of 200kg. **Maximum Arresting Force:** Impact force on user is kept below 6kN (in the event of a fall). **Lanyard Extension:** In the event of a fall lanyard may extend an additional length of 1.75m. **Compatibility:** Designed for use with Capital Safety approved harnesses, components or systems, or as recommended by a competent person.

**Standards:** AS/NZS 1891.1. **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety - Australia & New Zealand  
Australia: 1800 245 002 | New Zealand: 0800 212 505  
www.capitalsafety.com.au  
sales@capitalsafety.com.au

