

FORCE2™ WIRE CABLE
LANYARDS

THE NEXT REVOLUTION IN LANYARD TECHNOLOGY



THE NEW AND IMPROVED FORCE2™
SHOCK ABSORBING LANYARD RANGE

LIGHTEST, STRONGEST, SMALLEST SHOCK
ABSORBER IN THE WORLD



Contact Capital Safety for more
information on DBI-SALA's range of new
FORCE2™ Shock Absorbing Lanyards or
visit www.FORCE2.capitalsafety.com.au.
Alternatively scan the QR Code with your smart
phone/tablet using a QR scanner/reader.
(QR readers are available for free from your device's app store.)



THE ULTIMATE IN FALL PROTECTION

PRODUCT SHEET

FORCE2™ WIRE CABLE LANYARDS

ELIMINATING THE SHOCK FACTOR FOR SAFE & SECURE CONNECTIONS

Ideal for Fall Arrest, Work Positioning and Restraint

DBI-SALA shock absorbing lanyards combine strength and ease of use providing a safe and secure means of connecting your fall protection harness to a secure anchorage point. They are designed to quickly and effectively arrest a fall, whilst minimising shock loads on the body.

FORCE2™ WIRE CABLE SHOCK ABSORBING LANYARDS



Z10204545WR



Z12204545WR



FEATURES

- Lightest, strongest and smallest shock absorber in the world, 66% smaller and 40% lighter
- Minimises shock loads on the body limiting the arresting forces to under 6kN in the event of a fall
- Shock absorber includes Hi-10™ Energy Management Material protected by a rugged and durable soft cover
- Lanyard and shock pack stitching visible for easy inspection
- PVC coated wire cable for use in harsh environments, provides the ultimate in durability and longevity
- Stainless steel connectors available to reduce the risk of corrosion whilst maintaining maximum strength
- 16kN gate strength on all karabiners, removes the risk of accidental disengagement from excessive gate loadings
- Protected labels for durability and longevity
- Rated to 160kg - ideal for all workers regardless of shape, size and weight
- i-Safe™ enabled to track inspections, control inventory and manage information
- Ideal for use in all kinds of industrial environments and applications



Indicates the product utilises triple action karabiners making them ideal for use in mining applications

Specifications:

Part Number	Connectors		Length	Weight (Approx.)	Tails
	Harness	Anchorage			
Z10204545WR	R-119	R-119	2m	0.00kg	Single
Z12204545WR	R-119	R-119	2m	0.00kg	Twin

Cable: PVC coated 6mm galvanised cable. **Thread:** Polyester. **Hooks & Karabiners:** Refer to separate product information sheets. **Capacity:** 50-160kg (combined weight of person, tools, clothing, etc.). **Minimum Breaking Strength:** 15kN. **Activation:** Activates at a minimum force of 200kg. **Maximum Arresting Force:** Impact force on user is kept below 6kN (in the event of a fall). **Lanyard Extension:** In the event of a fall lanyard may extend an additional length of 1.75m. **Compatibility:** Designed for use with Capital Safety approved harnesses, components or systems, or as recommended by a competent person. **Standards:** AS/NZS 1891.1. **Country of Origin:** Australia.

Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety - Australia & New Zealand
 Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

