

Ideal for working in confined spaces and rescue applications!

8000000 - 2.13m Aluminium Tripod

- Fall arrest rated for 2 workers
- Lightweight and portable, requires only one person to set up
- Adjustable locking legs for added versatility
- · Complete with safety chain to prevent movement and safety feet that incorporate a rubber sole for flat surfaces and spiked edges for slippery surfaces
- · Durable corrosion resistant aluminium and heat treated cast aluminium construction
- Also available in 2.74m
- Meets or exceeds all applicable industry standards



1800 245 002 (AUS) 0800 212 505 (NZ) Head Office and Manufacturing 20 Fariola Street Silverwater NSW 2128 Australia Phone: +61 2 9748 0335 Fax: +61 2 9748 0336 Email: sales@capitalsafety.com.au www.sala.com.au

DBI-SALA is a brand of Capital Safety

PRODUCT NEWS


ALUMINIUM TRIPODS

Lightweight and Portable DBI-SALA aluminium tripods are lightweight and portable without sacrificing strength or durability, they are easily set up by one worker and can be transported from one location to another just as easily. Adjustable locking legs adjust quickly in increments for added versatility and are kept in position with locking push pins.

Ultimate Safety The heat treated cast aluminium head incorporates a built-in pulley system to rout the lifeline of mechanical device directly over opening. Also equipped with drop forged steel eyebolts for use as anchorage point for secondary or back-up system, designed to allow the eyebolt to hang plumb regardless of surface configuration. Complete with quick-mount bracket for attachment of DBI-SALA

mechanical device for ease of use, additional (back-up) mechanical devices can be mounted to tripod with optional bracket/ pulleys.

Tripod Accessories For ease of use and added flexibility. DBI-SALA offers several handy accessories for tripods as outlined to the right.



· Attaches to the tripod eye bolt for routing the back-up winch or SRL Cable Steel

8003238 Leg Mount Pulley

- · Attaches to tripod leg for routing the back-up winch or SRL cable
- Aluminium



- Attaches to tripod leg
- Mates with winch or SRL bracket
- Use with back-up system

Dimensions	8000000		8000010	
	Minimum Height	Maximum Height	Minimum Height	Maximum Height
Storage Length	1778mm		2591mm	
Hole diameter spanned	584mm	813mm	838mm	1118mm
Overall height	1727mm	2362mm	2413mm	3048mm
Available lift height	1245mm	1880mm	1930mm	2565mm
Height increments	76mm		76mm	
Spread of legs inside feet	1118mm	1600mm	1651mm	2134mm
Spread of legs outside feet	1473mm	1956mm	2007mm	2515mm

Specifications: Aluminium Tripods			
Part Numbers	8000000 - 2.13m (7'), 8000010 - 2.74m (9')		
Weight	8000000 - 21.3kg, 8000010 - 25.4kg		
Rated working load	158kg for work positioning or personnel riding applications; 140kg for fall arrest applications		
Material	Predominantly aluminium and zinc plated steel		
Compatibility	Designed for use with DBI-SALA approved harnesses, components or systems or as recommended by a competent person		
Accessories	Mechanical devices, snatch block, leg mount pulley, tripod mounting base, carry bag (9503094 or 9503095)		
Standards	Exceeds OSHA, ANSI Z359.1, ANSI A10.14, (Classified by Underwriters Laboratories Inc)		
Country of origin	United States		

Special Instructions / Conditions of Use

Reading user instruction manual prior to use is essential

ISO 9001 - With a full quality assurance program certified under ISO 9001, DBI-SALA supplies the industry with a quality range of safety products to provide added security. That's why we back each of our fall protection and rescue systems with the best training, technical assistance and customer service in the business. It makes life easier for you and safer for your workers.



1800 245 002 (AUS) Call 1800 2.12 505 (NZ) Head Office and Manufacturing 20 Fariola Street Silverwater NSW 2128 Australia Phone: +61 2 9748 0335 Fax: +61 2 9748 0336 Email: sales@capitalsafety.com.au www.sala.com.au DBI-SALA is a brand of Capital Safety