TOTO

MW9743084CEFG

Guinevere® WASHLET®+ C5 One-Piece Toilet - 1.28 GPF



TORNADO FLUSH







PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF (4.8 LPF). Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with SoftClose seat and Polished Chrome trip lever. Toilet shall be TOTO Model MW9743084CEFG#01.

See SW3084T40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC®), EPA WaterSense®, State of Massachusetts, City of Los Angeles, and
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use when installed with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements







FEATURES

- Concealed supply connection for seamless installation
- High-efficiency TORNADO FLUSH® system 1.28 GPF (4.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Decorative one-piece with skirted design
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl and WASHLET+ C5 and tank set
- EWATER+® auto-cleans wand after every use
- PREMIST® automatically mists the bowl before each use
- Convenient slim wireless remote with illuminated touchpad

MODELS

MW9743084CEFG (#01)

With CEFIONTECT ceramic glaze, WASHLET+ C5

CST974CEFGAT40 Elongated bowl with CEFIONTECT

SW3084T40 WASHLET+ C5

COLORS/FINISHES

#01 Cotton

OPTIONAL COMPONENTS

- **TSU03W.10R** 10" Unifit Rough-In
- **TSU03W.14R** 14" Unifit Rough-In
- THU458(#01, #BN, #PN)

Trip Lever (Cotton, Brushed Nickel, Polished Nickel)

SPECIFICATIONS


Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Water Surface	7-7/8" x 9-7/8"
Trap Diameter	2-1/8"
Rough-in	12" (10" and 14" options available)
Trap Seal	2-3/16"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	MW9743084CEFG: 120 lbs SW3084T40: 16.5 lbs
Shipping Dimensions	MW9743084CEFG 30" L x 19" W x 29-5/8" H ¹ x 18-1/2" H ² SW3084T40 23-5/8"L x 18-5/8"W x 7-5/8"H

See SW3084T40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS

**GFCI outlet of 120V, 10amps.
Washlet power cord is 4' long with 3 prongs.

