




85 mm

- ✓ Ø4 mm miniature housing
- ✓ Focused RED light source
- ✓ IO-Link
- ✓ Calibrated range
- ✓ Embeddable
- ✓ Immune to mutual interference



Cable type



Pigtail type

OPTICAL DATA		INTERFACE	
Sensing range typ. max.	0...85 mm ¹	Sensitivity adjustment	no
Operating range	0...70 mm ¹	Indicator LED, green	Excess gain
Light source	LED, red 630 nm	Indicator LED, yellow	Sensing state
Light spot size (distance)	Ø 5 mm (10 mm)	IO-Link	✓
	Ø 20 mm (50 mm)	MTTF (@40°C)	664 y

¹Object with 90% reflectance (standard white paper)



ELECTRICAL DATA		MECHANICAL DATA	
Supply voltage range (U _b)	10...30 VDC	Enclosure rating	IP67
Residual ripple	≤ 10% V _{pp}	Ambient temperature operation	-25...+65°C
Output current	≤ 100 mA	Shock and vibration	IEC 60947-5-2
Signal PNP high/low	≤ (U _b -2.0 V)/approx. 0 V	Weight (cable/connector/pigtail)	30 g / 12 g
Signal NPN high/low	Approx. U _b /≤ 2.0 V	Housing material	V2A stainless steel
Power consumption (no load)	≤ 12 mA	Optics material	PBT / PMMA
Response time ¹	≤ 500 μs (normal)/≤ 1 ms/≤ 200 μs	Cable type	PUR, 2 m, 3-wire
Switching frequency ¹	≤ 1 kHz (normal)/≤ 500 Hz/≤ 2.5 kHz	Pigtail type	PUR, L=0.35 m, Molex 3-pin
Short circuit protection	✓	Connector type	M8 3-pin
Voltage reversal protection	✓		

¹By default, "Normal" mode. "Fine" and "Fast" modes selectable via IO-Link.

SENSING RANGE

EXCESS GAIN

Target	Operating range	Sensing range max.
90%	0...70 mm	0...85 mm




IO-LINK FUNCTIONALITIES

IO-Link version	1.0
SIO mode	Supported
Process data	Detection state & stability alarm
Baudrate	COM2 (38.4 kBaud)
Special functions	Output configuration, output timing, sensitivity, sensor mode, detection counter, teach command, event flags, maximum and actual sensor temperature

IO-Link specifications and IODD files may be downloaded from www.contrinex.com (Download section)

WIRING DIAGRAM



AVAILABLE TYPES

Part number	Part reference	Polarity	Connection	Output (A1)
620-600-464	LTR-D04MA-NLK-403-504	PNP	PUR, 2 m, 3-wire	Light-on/IO-Link
620-600-465	LTR-D04MA-NLK-403-505	PNP	Pigtail, 0,35m, Molex 3 pins	Light-on/IO-Link

Note: additional suffix can appear to indicate a revision version or a special version.

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines. Terms of delivery and rights to change design reserved.