



Detail Paint

Metal Restoration Paint

- Fast Drying for Quick & Easy Handling
- Replicates the Look of Various Metals
- Resists Corrosion & Abrasion
- Professional Use

POR-15® Detail Paint provides professional grade finishes that reproduce the original look of cast parts. POR-15® Detail Paint is perfect for water pumps, intake manifolds, and master cylinders. Designed to protect against rust, all the colors are developed to have a low sheen, and will not yellow to keep your restored component looking factory new. POR-15® Detail Paint is formulated to provide maximum corrosion resistance and protect metal substrates against weather, sunlight, oil, and water. For use on bare metal, or for the ultimate protection use over POR-15® Rust Preventive Coating.



PRODUCT	SIZE	CODE
Cast Aluminum	Spray 15 oz.	41618
Cast Iron Gray	Spray 15 oz.	41718
Stainless Steel	Spray 16 oz.	41818

Applications: (For use over prepared metal surfaces)

- Cylinder heads
- Engine blocks
- Water pumps
- Industrial Interior / exterior
- New construction
- Repaints
- Railings
- Storage tanks
- Machinery
- Structural steel
- Piping
- Steel decking



Product Information

Detail Paint

Metal Restoration Paint



Product Description

POR-15® Detail Paint provides professional grade finishes that reproduce the original look of cast parts. POR-15® Detail Paint is perfect for water pumps, intake manifolds, and master cylinders. Designed to protect against rust, all the colors are developed to have a low sheen, and will not yellow to keep your restored component looking factory new. POR-15® Detail Paint is formulated to provide maximum corrosion resistance and protect metal substrates against weather, sunlight, oil, and water. For use on bare metal or for the ultimate protection use over POR-15® Rust Preventive Coating.

Application Information

Surface must be clean, dry and free of oil and other contaminants before painting. Protect surrounding areas from spray mist. If being used to topcoat POR-15, spray while POR-15® is dry to the touch with slight finger drag, normally 2 – 6 hours. If POR-15 has dried, wait 24 hours then lightly sand or scuff surface with pad or 320 sand paper. If scuffing or sanding is not desired, use POR-15 Self Etching Primer over cured POR-15® without sanding, then topcoat over the primer.

- Shake can at least one minute before and occasionally during use.
- Spray surface with steady, even strokes at a distance of 8 to 10 inches. Several light coats give a better finish than one heavy coat. For best results, recoat within 1 hour or after 24.

Safety Information

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. In contact with water releases flammable gases, which may ignite spontaneously. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

(Cast Aluminum)

⚠WARNING: This product can expose you to ethyl benzene or Toluene chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

(Cast Iron Gray)

⚠WARNING: This product can expose you to ethyl benzene, Carbon Black or Toluene chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

(Stainless Steel)

⚠WARNING: This product can expose you to ethyl benzene or Toluene chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

PREVENTION: Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Handle under inert gas. Protect from moisture. Do not allow contact with water. Do not breathe dust/fume/gas/mist/vapors/spray.

RESPONSE: IF INHALED: Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. **IF ON SKIN:** Wash with plenty of water. In case of fire: Use for extinction: CO₂, sand, extinguishing powder. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

CLEANUP: To prevent clogs in spray nozzle, hold can upside down and spray until clear gas appears. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT puncture, incinerate or compact.

STORAGE: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store in a dry place. Store in a closed container. Keep container tightly closed.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations.

ADDITIONAL PRECAUTION STATEMENTS: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents maybe harmful or fatal. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear a NIOSH approved respirator during and after application. Follow respirator manufacturer's directions for respirator use.

FOR PROFESSIONAL USE. KEEP OUT OF REACH OF CHILDREN.

Metallic Paint products Does Not Exceed 1.25 MIR

Refer to Material Safety Data Sheet available upon request for further safety and handling information.

P.O.R. PRODUCTS 800-457-6715
PORproducts.com

P.O.R. Products, 38 Portman Rd, New Rochelle, NY 10801

© 2018 P.O.R. Products © POR-15 is a registered trademark of P.O.R. Products.