



Dry Time Accelerator

Additive for POR-15®
Rust Preventive Coating

- Faster Recoat and Dry Time
- Enough for 8 gallons of POR-15 Rust Preventive Coating
- Easy-To-Use Measurement Container
- Professional Use

POR-15® Dry Time Accelerator is an additive specially formulated for use with POR-15® Rust Preventive Coating. Dry Time Accelerator is designed to accelerate the cure time of POR-15® Rust Preventive Coating by 30-50% without affecting the ultimate physical properties. Developed to allow for a more efficient production environment, Dry Time Accelerator reduces recoat and dry time and enables you to move on to the next phase faster, without compromising product performance.

The accelerator is added to POR-15® Rust Preventive by volume and should be thoroughly mixed. Once mixed in typically the cure time of the POR-15® Rust Preventive is reduced by 30-50%. **Important: Adding the accelerator drastically reduces the cure time (time you have to apply to your substrate) and under humid and warmer conditions the dry time is significantly quicker.**

We recommend testing to ensure your specific needs are met. One 8 oz. bottle of POR-15® Dry Time Accelerator is enough for 32 quarts or 8 gallons of POR-15® Rust Preventive Coating.



PRODUCT	SIZE	CODE
Dry Time Accelerator	8 oz.	40616

Features:

- Accelerate the cure time 30-50%
- Does not affect the ultimate physical properties of POR-15 Rust Preventive Coating
- Move on to the next phase faster
- One 8 oz. bottle is enough for 32 quarts or 8 gallons



Product Information

Dry Time Accelerator

Additive for POR-15® Rust Preventive Coating



Product Description

POR-15® Dry Time Accelerator is an additive for use only with POR-15 Rust Preventive Coating to reduce recoat and dry time and accelerate the cure time by 30 – 50%, using a blend catalyst and solvents to enhance the chemical reaction.

Application Information

DIRECTIONS: Add 1 ounce of POR-15 Dry Time Accelerator to 1 gallon of POR-15 Rust Preventive Coating and stir to mix thoroughly (do not shake). The dry time of POR-15 Rust Preventive Coating is dependent on temperature and humidity even with the addition of this accelerator. Spot testing is recommended.

IMPORTANT: POR-15 Dry Time Accelerator is designed for use with POR-15 Rust Preventive Coating only and its use with other products is not recommended.

Safety Information

DANGER! FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN, EYE AND RESPIRATORY IRRITATION.

WARNING! Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose and throat and irritation.

KEEP OUT OF REACH OF CHILDREN - PROFESSIONAL USE

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure suspected to cause damage to organs, fertility, genetic defects or cause cancer.

USE ONLY WITH ADEQUATE VENTILATION.

Do not breath vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

Can be absorbed through skin. May cause liver, kidney, thyroid, cardiovascular and/or reproductive system damage. Wear protective eye/face protection, gloves and clothing.

FIRST AID: If medical advice is needed, have product label available. In case of eye contact, flush immediately with plenty of water, remove contact lenses if present and easy to do. Continue rinsing eye for at least 15 minutes. Get medical attention immediately. For skin (or hair), immediately remove/take off all contaminated clothing; wash skin thoroughly with soap and water. If you experience difficulty breathing, leave area to obtain fresh air, If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, Call physician or Poison Control Center immediately,

Only use outdoors or in well ventilated area. Keep away from heat, spark and flame. No smoking. Prevent build-up of vapor by opening all windows and doors to achieve cross-ventilation. Vapor may cause flash fire. In case of fire use dry chemical foam, carbon dioxide, or alcohol-resistant foam. Do not use water as an extinguisher. Avoid release to the environment. Prevent from reaching drains, sewer or waterway. Toxic to aquatic life. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

⚠WARNING: This product contains a chemical known to the State of California to cause cancer.

Volatile Organic Content (VOC): less than 870 g/L

Refer to Material Safety Data Sheet available upon request for further safety and handling information.

P.O.R. PRODUCTS 800-457-6715
PORproducts.com

P.O.R. Products, 38 Portman Rd, New Rochelle, NY 10801

© 2018 P.O.R. Products © POR-15 is a registered trademark of P.O.R. Products.