

Nexus Grippa-Fast 200 Adhesive

TECHNICAL DATA SHEET

DESCRIPTION & USES

Nexus 200 is ideal for bonding carpet gripper, woods, metal trims, metal nosing, aluminium & many other types of products where a quick bond is required to concrete, timber and most other common building substrates. **Nexus 200** has excellent resistance to high temperatures and water.

PREPARATION

All surfaces must be clean & sound, free of dust and any other contaminants that may affect bond.

APPLICATION

Apply thin bead of adhesive to one surface. Press the two surfaces to be bonded firmly together. Pressure may need to be applied to keep the two surfaces in contact while adhesive cures. Large extrusions should also be secured with appropriate fixing screws.

CURING TIME

Nexus 200 is a moisture cure system. Allow approx. 1 hour curing time. This process may be accelerated by spraying a light mist of water to one of the surfaces. Thick beads will take longer to cure and will have a weaker bond than a thinner bead. The thicker the bead of **Grippa Fast 200** the more the product will tend to foam.

CLEAN UP

Remove any wet adhesive with suitable solvent cleaner before it cures. When cured remove by mechanical means.

Typical Properties

Appearance	Brown Liquid
Viscosity	Thin Liquid
Packaging	500ml Bottles
Shelf Life	6 Months

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
info@nexusadhesives.com.au
www.nexusadhesives.com.au