

# Nexus 440 Brushable Skirting Contact

## TECHNICAL DATA SHEET

### DESCRIPTION

**Nexus 440** is a solvent based neoprene contact adhesive used for fixing vinyl skirting and other common flooring materials where a quick contact bond is required to plaster, timber and metal substrates.

### METHOD OF APPLICATION

To obtain the best results, the materials to be bonded should be dry, clean and free from dust, grit, oil, grease and other contaminants that may affect final bond.

Apply an even coat of adhesive to both surfaces by brush or roller. On porous surfaces a second application may be required.

Allow solvent to evaporate and adhesive to become tacky. Place the surfaces together making sure that they are correctly positioned beforehand as no adjustment is possible after the surface has met.

Press both surfaces together, making sure sufficient pressure is applied to bring both surfaces into close contact.

### CLEAN UP

Clean tools immediately after use with **Nexus 490** solvent cleaner.

### Typical Properties

Appearance	Light yellow liquid
Viscosity	Brushable liquid
Coverage	3 - 4m <sup>2</sup> per litre
Packaging	1, 4 & 20 Litre

**Note:** Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

March 2020

**Nexus Adhesives Pty Ltd**  
ABN 61 121 120 036

42 Healey Road  
Dandenong South VIC 3175 Australia  
Tel +61 3 9706 4022  
Fax +61 3 9706 4122  
info@nexusadhesives.com.au  
www.nexusadhesives.com.au