

Nexus 445 Spray Contact

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 445 is a general purpose solvent based sprayable contact adhesive used for fixing laminating or laminex to various types of wood such as chipboard and hardboard.

Nexus 445 is also suitable for polyurethane foams, supported PVC, fabric, leather, rubber sheet and extrusions to each other.

METHOD OF APPLICATION

To obtain the best possible results, the materials to be bonded should be dry, clean and free from dust, grit, loose materials, oil or grease.

Using conventional spray equipment, apply an even coating of adhesive to both surfaces to be bonded.

Allow the solvent to evaporate before bonding the materials. On absorbent materials such as leather and chipboard, bonding may be within a matter of 2-3 minutes of application. On non-absorbent materials such as formica and metal a minimum of 15 minutes should be elapsed before the surfaces are bonded together.

Contact bond the surfaces together using firm pressure.

CLEAN UP

Clean tools immediately after use with **Nexus 490** solvent cleaner.

Typical Properties

Appearance	Opaque yellow liquid
Viscosity	Thin liquid
Coverage	6 - 8m ² per litre
Packaging	20 Litre

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
info@nexusadhesives.com.au
www.nexusadhesives.com.au