

# Nexus 460 Vinyl Seam Sealer

## TECHNICAL DATA SHEET

### DESCRIPTION

**Nexus 460 Vinyl Seam Sealer** is a solvent based adhesive designed for the chemically welding of domestic vinyl sheet flooring seams.

### DIRECTIONS FOR USE

All seams must be clean and dry prior to seam sealing.

Transfer **460 Vinyl Seam Sealer** to applicator bottle.

Place masking tape over centre of seam, cut tape at seam in floor.

Starting at one end of seam insert applicator tip into seam and apply a continuous bead along the entire length of the seam.

Allow approx. 10 minutes and remove tape.

Avoid excess seam sealer on surface of floor covering.

### CLEAN UP

Clean tools immediately after use with **Nexus 490** cleaner.

**Nexus 490** is not suitable for use on Vinyl, Carpets or any finished surface.

**PACKAGING** 500ml

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

### Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road  
Dandenong South VIC 3175 Australia

Tel +61 3 9706 4022

Fax +61 3 9706 4122

info@nexusadhesives.com.au

www.nexusadhesives.com.au