

Nexus 485 Outdoor Grass Adhesive

TECHNICAL DATA SHEET

DESCRIPTION & USES

Nexus 485 Outdoor Grass Adhesive is a solvent based outdoor grass adhesive used for the installation of synthetic grass carpet in outdoor applications.

The adhesive will adhere to most common absorbent building substances.

METHOD OF APPLICATION

The surface should be clean, dry, free from dust, grease, oil, and contaminants that may affect final bond.

Concrete must be cured and free of any curing compounds.

Refer to Australian Standard 2455- Textile Floor Coverings Installation Practise- General.

Spread the adhesive with the recommended "V3" 3.2mm x 1.6mm x 3.2mm notched trowel and allow a short time to tack-up before placing carpet into wet adhesive.

Tack up time can be determined by placing a small piece of synthetic grass into the adhesive.

"Legs" of adhesive should be apparent when the synthetic grass is pulled away.

Check to ensure that complete transfer of adhesive to the floorcovering has occurred.

Typical Properties

Appearance Green thick paste Viscosity Trowelable thick paste Specific Gravity Approx 1.0

Open Time Approx 15-20 mins

Solids 55-60%

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road Dandenong South VIC 3175 Australia **Tel** +61 3 9706 4022 Fax +61 3 9706 4122 info@nexusadhesives.com.au www.nexusadhesives.com.au