

Nexus 510 Acrylic Floor & Wall Primer

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 510 Primer is a water based acrylic primer designed to prime absorbent substrates prior to the application of water-based adhesives.

FOR PRIMING

Most highly absorbent substrates such as concrete, timber, solid plaster, plasterboard, cement sheet and cementitious screeds.

STANDARDS

Australian/NZ Standard 2455.1.2007 – “Textile Floor Coverings Installation Practice” & current AS1884-2012

SURFACE PREPARATION

All surfaces to be primed should be dry, smooth, and free of any contaminants that may affect final bond. It is highly recommended that all absorbent sub floors be primed with **Nexus 510 Primer** prior to the application of adhesive.

The minimum sub floor temperature prior to commencing preparation or primer application is 10°C.

APPLICATION

Nexus 510 Primer should be applied evenly over the entire sub floor by Soft Broom or Brush. Highly absorbent sub floors may require a second coat of **Nexus 510 Primer**. Allow first coat to dry prior to applying further coats.

Typical Properties

Base:	Acrylic
Appearance:	White Liquid
Viscosity:	Thin Liquid
Shelf Life:	12 months in sealed container at 20°C
Packaging:	15 Litre
Freezability:	Avoid Freezing

CLEAN UP

Clean tools immediately after use with warm soapy water.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
info@nexusadhesives.com.au
www.nexusadhesives.com.au