

# Nexus 520 Crosslinking PVA

## TECHNICAL DATA SHEET

### DESCRIPTION

**Nexus 520** is a high performance one part Crosslinking PVA based adhesive.

It is designed for bonding a wide range of timbers, Ply, Particle Board, MDF and tongue & grooved flooring.

**Nexus 520** has good water resistance and bond strength after 24 hours. Full cure within 5 – 7 days.

### SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond.

All edges should be square to ensure maximum bond strength.

### DIRECTION FOR USE

Apply **Nexus 520** by bottle, brush or roller to suite the type of installation.

Assemble within a couple of minutes and then clamp or secure together until adhesive has set.

Allow adhesive 24 hours to cure prior to use.

### CLEAN UP

Do not allow adhesive to dry on floor coverings.

Clean excess adhesive immediately using a lightly damp cloth.

### Typical Properties

Appearance	White Liquid
Viscosity	Medium Liquid
Shelf Life	12 months in sealed container at 20°C
Packaging	500ml, 4Lt & 15 Litre containers

**Note:** Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

**Nexus Adhesives Pty Ltd**  
ABN 61 121 120 036

42 Healey Road  
Dandenong South VIC 3175 Australia  
**Tel** +61 3 9706 4022  
**Fax** +61 3 9706 4122  
info@nexusadhesives.com.au  
www.nexusadhesives.com.au