

ARDEX K65

Single Part Timber Leveller

ARDEX K65 is an advanced fibre reinforced smoothing and levelling compound for internal use, featuring MICROTEC technology that is designed to rapidly smooth and level new and existing substrates prior to applying a floor finish.

LOCATION

- Internal sub-floors

SUBSTRATES

- New and existing strip timber
- Particleboard, plywood, concrete
- Compressed fibre cement flooring, terrazzo, quarry and ceramic tiles
- Concrete subfloors with electric under floor heating

FLOOR COVERINGS

- Carpet, vinyl, LVT, carpet tiles, floating floors

COVERAGE

- 4.5m² at 3mm thickness

THICKNESS

- From 3.0mm to 20mm in one application without aggregate
- For areas requiring a thickness over 20mm to a maximum of 50mm, ARDEX K65 must be mixed with a well washed and dried 2 – 5mm aggregate

DRYING TIME

- Drying time is dependent on jobsite temperature, humidity, installation thickness and floor covering type. (Based on 23°C and 50% RH.)
- Walkable from 2-3 hours. Conventionally laid carpet and floating floors can be installed after 24 hours. Direct stick applications such as vinyl flooring after 48 hours

PACKAGING

- 20kg bag

CODE

38352



ARDEX K65 QUICK FACTS

- Ideal for timber substrates
- Rapid hardening - walkable in just 2 hours
- Microtec Fibre-Reinforced

