

CRACK INJECTION

ARDEX RA 88

Multi-Purpose Epoxy Repair Adhesive

ARDEX RA 88 is a two component, high performance ceramic blend epoxy. No-drip, non-sag, repair adhesive perfect for horizontal, vertical and overhead use (trowelable). Fast cure time (approx. 2 hours) and when cured, over twice as strong as standard concrete. Ideal for use as a repair adhesive for almost any material, including metal, concrete, brick, wood, stone, block and other substrates. It can also be used for repairing holes, spalls and cracks in concrete, repairing rotted wood, installing anchor bolts and repairing hand rails.

LOCATION

It can also be used for repairing holes, spalls and cracks in concrete, repairing rotted wood, installing anchor bolts and repairing hand rails.

SUBSTRATES

Almost any material, including metal, concrete, brick, wood, stone, block and other substrates.

COVERAGE

Approx. 6 linear metres with a bead thickness of 6 x 6mm.

COLOURS

Grey

DRYING AND CURING

Open to full traffic in 2–3 hours, ready to receive paint in 2–3 hours.

VOC CONTENT

60g/L

PACKAGING

245mL cartridge



ARDEX RA 88 QUICK FACTS

- Non-sag - Perfect for overhead and vertical repairs
- High strength - Stronger than concrete > 55Mpa
- Trowelable and cures underwater



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE