

2.0mm EXCELON IMPERIAL TEXTURE

VINYL COMPOSITION TILE

Approved flooring for Department of Communities – Housing

PRACTICAL

- Economical
- Modular 2.0mm x 300mm x 300mm tile format
- Quick to install
- Easy to repair



DURABLE

- > 80% natural stone
- Outstanding stability and durability
- Improved surface with excellent resistance to soiling

APPLICATIONS

- Housing
- Retail
- Education
- Transport

TECHNICAL DATA

Product Type (ISO 10595)	Vinyl Tile
Manufactured in	South Korea
Tile Size (ISO 24342)	300mm x 300mm
Overall Thickness (ISO 24346)	2.0mm
M ² /Carton	4.95m ²
Tiles/Carton	55
Slip Resistance (AS 4586): Wet Pendulum (Slider 96) Oil-Wet Inclining Platform	P2 (No polish) R9 (No polish)
Fire Resistance (ISO 9239-1) Critical Radiant Flux (CRF) Smoke Development Rate	≥11kW/m ² ≤750%. minutes
Classification (ISO 10874)	Commercial: 33  Industrial: 42 

Visit www.armstrongflooring.com.au or contact Customer Service 1800 632 624 for technical data, installation, cleaning and maintenance instructions. Please note: Recommendations are for guidance only, refer to relevant local, state, and federal construction codes and standards for requirements.

Contact:

Armstrong Flooring Pty Ltd
29 – 39 Mills Road, Braeside, 3195 Victoria Australia
For further information and samples:
Australia Freecall 1800 632 624
Email customer_services@armstrongflooring.com or visit us on the web
www.armstrongflooring.com.au