

SAFETY DATA SHEET

Page 1 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

1. Substance/preparation and company identification

1.1 Product Identifier

Nexus 485 Synthetic Grass Adhesive

1.2 Product use and description

Solvent based synthetic grass and outdoor carpet adhesive

1.3 Details of the supplier of the safety data sheet

Nexus Adhesives Pty Ltd
42 Healey Road, Dandenong South.
Victoria 3175 Australia
Telephone: +61 3 9706 4022
Telefax number: +61 3 9706 4122

1.4 Emergency telephone number

0417 489 877 [within Australia]

2. Hazard identification

2.1 GHS Hazard Classification:

Hazardous according to criteria of WHS and ADG codes and regulations.

2.2 Hazard Statements

H225	Highly flammable liquid and vapour	Cat 2 Liq.
H304	May be fatal if swallowed and enters airways	Cat 1 Asp Tox.
H315	Causes skin irritation	Cat 2 Irrit.
H336	May cause drowsiness or dizziness	Cat 3 STOT SE
H400	Very toxic to aquatic life	Cat 1 Acute
H410	Very toxic to aquatic life with long-lasting effects	Cat 1 Chronic

2.3 Hazard Pictogram



Flame

Exclamation
Mark

Health Hazard

Environmental
Hazard

SAFETY DATA SHEET

Page 2 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

2.3 Signal Word

Danger

2.4 Precautionary Statements - Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fumes/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

2.5 Precautionary Statements – Response

P312	Call a POISON CENTER/ doctor if you feel unwell.
P321	Specific treatment (see ... on this label).
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/
P303+361+353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362+364	Take off contaminated clothing and wash it before reuse.
P370+378	In case of fire: Use ... to extinguish.

2.6 Precautionary Statements – Storage

P405	Store locked up.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.

2.7 Other hazards

P501	Dispose of contents/container in accordance with local/regional/national regulations.
------	---

3. Composition/information on ingredients

Chemical nature

SAFETY DATA SHEET

Page 3 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Paste

Chemical Name	CAS No.	Conc (%w/w)	Classification
Naphtha (petroleum), hydrotreated light	64742-49-0	< 50%	H304 May be fatal if swallowed and enters airways
Heptane	142-82-5	< 50%	H225 Highly flammable liquid and vapour H304 May be fatal if swallowed and enters airways H400 Very toxic to aquatic life H410 Very toxic to aquatic life with long-lasting effects H315 Causes skin irritation H336 May cause drowsiness or dizziness
Naphtha (petroleum), hydrotreated heavy	64742-48-9	< 40%	H304 May be fatal if swallowed and enters airways H227 Combustible liquid
n-Hexane	110-54-3	< 5%	H225 Highly flammable liquid and vapour H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure H304 May be fatal if swallowed and enters airways H411 Toxic to aquatic life with long-lasting effects H315 Causes skin irritation H336 May cause drowsiness or dizziness
Non-hazardous ingredients	-	To 100	

4. First-aid measures

4.1 Description of first aid measures:

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air and seek medical attention if breathing becomes difficult. Apply artificial respiration if not breathing, perform CPR if necessary.

SAFETY DATA SHEET

Page 4 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

On skin contact:

Immediately remove contaminated clothing, Wash thoroughly with soap and water. Seek medical attention in event of irritation.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist without delay.

Removal of contact lenses after an eye injury should be undertaken by skilled personnel.

On ingestion:

Rinse mouth immediately and then drink plenty of water, DO NOT induce vomiting unless directed to do so by a physician. Seek medical attention immediately.

Advice to doctor:

Treat symptomatically

4.2 Most important symptoms and effects, both acute and delayed:

If inhaled:

May cause nausea and vomiting

On skin contact:

Cause burns. May cause sensitisation by skin contact.

On contact with eyes:

Cause burns. Cause severe inflammation and may damage the cornea.

On ingestion:

May cause nausea and vomiting.

4.3 Indication of any immediate medical attention and special treatment needed

Seek medical attention

5. Fire-fighting measures

5.1 Suitable extinguishing media:

Water fog, dry extinguishing media, foam, carbon dioxide.

5.2 Special hazards arising from the substance and mixture

Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may results.

5.3 Advice for fire fighters:

Fire Fighting:

Alert Fire Brigade and tell them location and nature of hazard.

Full protective clothing and self-contained breathing apparatus when necessary.

Prevent, by any means available, spillage from entering drains or water course.

Use water delivered as a fine spray to control fire and cool adjacent area.

Avoid spraying water onto liquid pools.

SAFETY DATA SHEET

Page 5 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Fire/Explosion Hazard:

Combustible.

Moderate fire hazard when exposed to heat or flame.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid accidents, clean up immediately. Slippery when spilt. Personnel involved in the cleanup should wear full protective clothing.

Evacuate all unnecessary personnel. Eliminate all sources of ignition. Increase ventilation. Avoid generating dust. Stop leak if safe to do so. Isolate the danger area.

6.2 Environmental precautions

Do NOT let product reach drains or waterways. If product does enter a waterway, advise the Environmental Protection Authority or your local Waste Management. Use clean, non-sparking tools and equipment.

6.3 Methods and materials for containment and cleaning up

Contain and sweep/shovel up spills with dust binding material or use an industrial vacuum cleaner. Transfer to a suitable, labeled container and dispose of promptly. Recycle if possible.

7. Handling and storage

7.1 Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Use in well-ventilated area.

DO NOT enter confined spaces until atmosphere has been checked.

DO NOT allow clothing wet with material to stay in contact with skin.

Store in original containers.

Keep containers securely sealed.

No smoking, naked lights or ignition sources.

Store away from incompatible materials and foodstuff containers.

7.2 Conditions for safe storage, including any incompatibilities

Suitable container:

Metal can or drum

Packaging as recommended by manufacturer.

Check all containers are clearly labelled and free from leaks.

SAFETY DATA SHEET

Page 6 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Storage Incompatibility:

Avoid exposure to heat, naked flames and strong oxidising agents. Keep away from ignition sources.

7.3 Specific end use

See section 1.2 for further information

8. Exposure controls and personal protection

8.1 Control parameters

Australian Exposure Standards:

Chemical Name	CAS No.	TWA	STEL
Heptane	142-82-5	1640 mg/m ³ 400 ppm	2050 mg/m ³ 500 ppm
n-Hexane	110-54-3	72 mg/m ³ 20 ppm	Not Specified
Naptha (petroleum), hydrotreated heavy	64742-48-9	1200 mg/m ³ 171 ppm	Not Specified

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation of the working area.

Hand protection:

Suitable chemical resistant safety gloves (PVC)

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Respiration apparatus:

Self-contained breathing apparatus. Suitable half mask respirator with filter P2 (e.g. EN 143)

Environmental exposure control:

See section 6 for further information.

General safety and hygiene measures:

Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

9. Physical and chemical properties

Appearance:	Paste
Colour:	Green
Odour:	Typical hydrocarbon odour
Odour threshold:	No data available
pH value:	No data available
Melting/freezing point:	No data available
Initial boiling point:	>40 °C

SAFETY DATA SHEET

Page 7 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Flash point:	<-20 °C
Evaporation rate:	No data available
Flammability:	Highly Flammable
Vapour pressure:	No data available
Vapour density:	No data available
Relative density:	Approx. 1 kg/L
Solubility:	Insoluble
Partition coefficient:	No data available
Auto ignition temperature:	Not applicable
Viscosity:	Thick paste
Specific heat value:	No data available
VOC content:	No data available
% volatile:	No data available
Saturated vapour concentration:	No data available

10. Stability and reactivity

10.1 Reactivity

No particular risks of reaction with other substances in normal conditions of use.
Possible hazardous reaction with strong oxidising agents.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reaction

See Section 7.

10.4 Conditions to Avoid

None in particular. However, the usual precautions used for chemical products should be respected.

10.5 Incompatible materials and possible hazardous reactions

See Section 10.1

10.6 Hazardous decomposition products

Oxides of carbon and organic compounds.

11. Toxicological information

11.1 Information on route of exposure and symptoms

If inhaled:

SAFETY DATA SHEET

Page 8 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

May cause nausea and vomiting, can cause respiratory irritation in some person. The body's response to such irritation can cause further lung damage.

On skin contact:

May cause sensitisation and inflammation by skin contact. The material can accentuate any pre-existing dermatitis condition. Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into blood-stream through cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

On contact with eyes:

May cause severe inflammation and may damage the cornea.

On ingestion:

May cause nausea and vomiting.

11.2 Numerical measure of toxicity

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY CAS: 64742-48-9

LD50 (Oral): > 5000 mg/kg (rat)

LD50 (Dermal): > 3000 mg/kg (rat)

12. Ecological information

12.1 Ecotoxicity

No information available

12.2 Persistence and degradability

No information available

12.3 Bioaccumulative potential

No information available

12.4 Mobility in soil

No information available

12.5 Other adverse effects

No information available

13. Disposal considerations

13.1 Safe handling and disposal methods

Dispose of this material and its container, sending them to local company authorised for collection of hazardous waste.

13.2 Disposal of any contaminated packaging

SAFETY DATA SHEET

Page 9 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.

14. Transport information

14.1 UN Number

UN1133

14.2 UN proper shipping name

Adhesives containing flammable liquid

14.3 Transport hazard class(es)

Class 3 Flammable Liquids

Hazchem 3[Y]E

14.4 Packing group

III (ADG, IMDG, IATA)

14.5 Environmental hazards

Environmental hazards Yes

Marine pollutant Yes Symbol (fish and tree)

14.6 Special precautions for users

Transport in secure and safe packaging. Keep all containers upright. Transporter should be aware of emergency procedures in place in case of any accident or leakage. See Section 4-8 for further information.

14.7 Hazchem Code

Hazchem 3[Y]E

14.8 Other codes

ARD/RID

As above

IMDG

As above

IATA

As above

15. Regulatory information

15.1 Safety, health and environmental regulations specific for the product

Naphtha (petroleum), hydrotreated light 64742-49-0

Heptane 142-82-5

SAFETY DATA SHEET

Page 10 of 10

Date: 14/11/2016

Hazardous according to criteria of worksafe Australia
NEXUS 485 SYNTHETIC GRASS ADHESIVE

Revision: 0

Naphtha (petroleum), hydrotreated heavy 64742-48-9
n-Hexane 110-54-3

Found on the following regulatory lists:

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System – Consolidated Lists

International Agency for Research on Cancer (IARC) – Agents Classified by the IARC Monographs

15.2 Poisons schedule number

5

16. Other information

Any other intended applications should be discussed with the manufacturer.

Revisions:	Date	Sections Reviewed
0	14/11/2016	-

Contact	
Technical	Sales
0417489877	0448395091

Asterisk * in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agree property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.