

Nexus 430 Construction Adhesive

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 430 Construction adhesive is specifically developed for bonding most common materials used in the construction industry.

Nexus 430 is a high solids product that forms a very strong bond to most common building products including timber, plasterboard, MDF, particleboard, timber sheet flooring, concrete and metals.

PREPARATION

All surfaces must be clean & sound, free of dust and any other contaminants that may affect bond.

APPLICATION

Cut cartridge tip, fit nozzle and cut end to desired opening. (Approx 4-5mm) Apply beads of adhesive to one surface of product to be bonded. Press the two surfaces to be bonded firmly together. Apply pressure to keep the two surfaces in contact while adhesive cures. Fix with sufficient nails, screws or clamping to maintain contact.

CLEAN UP

Remove any wet adhesive with **Nexus 490**. When cured remove by mechanical means.

STORAGE/SHELF LIFE

Store in dry cool place / 12 months in unopened cartridge.

PACKAGING

320gm Cartridges

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
info@nexusadhesives.com.au
www.nexusadhesives.com.au