

Nexus 990 Carpet Latex

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 990 Carpet Latex is a Natural Latex compound for sealing raw edges of carpet and installing felt underlay to substrates.

METHOD OF APPLICATION

Prior to joining carpet seams with heat bond tape or seam sealer, apply **Nexus 990** to edge of carpet and allow drying.

Doing this helps prevent with loss of tufts and unraveling after seams have been trimmed.

When used to install felt underlay to subfloors apply a liberal amount to the subfloor and install underlay into wet latex.

CLEAN UP

Clean tools immediately after use with warm soapy water.

Typical Properties

Base:	Natural Latex
Appearance:	White Liquid
Viscosity:	Thin Liquid
Shelf Life:	12 months in sealed container at 20°C
Packaging:	1, 4 & 15 Litre
Odour:	Ammonia
Freezability:	Avoid Freezing

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

October 2013

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia

Tel +61 3 9706 4022

Fax +61 3 9706 4122

info@nexusadhesives.com.au

www.nexusadhesives.com.au