

Inspiring
Great
Spaces™

Armstrong®
FLOORING



TIMBERLINE PLUS
TRANSLATIONS PLUS
COMMERCIAL FLOORING
HETEROGENEOUS VINYL SHEET

TIMBERLINE PLUS TRANSLATIONS PLUS HETEROGENEOUS VINYL SHEET



TECHNICAL DATA		TIMBERLINE PLUS / TRANSLATIONS PLUS – P3/R10				
Type of floor covering		Heterogeneous Sheet Vinyl				
Manufacturing standard	ISO 10582	Type 1 Binder content				
Classification	ISO 10874	Commercial: 34 Very Heavy		Light Industrial 43 Heavy		
Surface treatment		PUR + Aluminum Oxide				
Wear resistance	EN 660-2	Group T				
Wear layer thickness	ISO 24340	0.7mm				
Total thickness	ISO 24346	2.0mm				
Roll length	ISO 24341	25m				
Roll width	ISO 24341	1.83m				
Weight/m ²	ISO 23997	2.78 kg/m ²				
m ² /Roll		45.75m ²				
Residual indentation	ISO 24343-1	≤ 0.1mm (PASS)				
Effect of castor chair	ISO 4918	PASS				
Colour fastness	ISO 105-B02 (method 3)	>6 (PASS)				
Impact sound isolation	ISO 140-8	4 dB				
Flexibility	ISO 24344 (method A)	20mm mandrel, no cracking (PASS)				
Chemical resistance		Good resistance (full tests can be supplied on request)				
Dimensional stability	ISO 23999	<0.40% (PASS)				
Curling after exposure to heat	ISO 23999	<8 mm (PASS)				
Seam strength	ISO 16906	PASS				
Fire Resistance – ISO 9239-1						
Critical radiant flux		≥8 kW/m ²				
Smoke development rate		< 750% min				
Pattern	Lithos Stone	Rustic Beech	Arcadian Oak, Linearis Alchemy, Mahogany	Oak	Solu, Obra, Luci, Calde, Blanc	
Plank size (within pattern) – nominal	N/A	Random lengths between 795-329mm x 65mm	1269mm x 180mm	Oak 1264mm x 90mm	Obra 1250 x 90, Luci 625 x 100, Solu, Calde, Blanc 625 x 112.5mm	
Pattern repeat (mm)	900 x 1250 (½ Dropped)	900 x 1250 (½ Dropped)	1800 x 1250	900 x 1250 (½ Dropped)	900 x 1250	
Slip Resistance AS 4586:2013 (2004)						
Surface Embossing	EC-2	EC-5	EC-5	EC-5	EC-5	
Appendix A: Wet Pendulum (Slider 96)	P3	P3	P3	P3	P3	
Appendix D: Oil-wet inclining platform	R10	R10	R10	R10	R10	
Installation	Full Spread adhesive. Install to AS1884:2012					
Seaming	Heat welded with matching weld rod, chemical seam seal (follow manufacturer's instructions)					
Recommended adhesive	Armstrong Flooring; Full spread SV-200, Coving & Accessories: SC-100 Contact Adhesive					
Applications	Interior commercial areas with high traffic and light industrial areas, e.g. Medical centres, nursing homes, offices, store rooms, production halls, department stores, schools, hospitals. Also suitable for residential applications.					
Manufactured	South Korea					
Instructions	Armstrong Flooring Pty Ltd instructions regarding adhesives, installation, cleaning and maintenance should be observed. Please contact Armstrong Flooring for details.					
NOTE: Printed images may vary from actual samples, variation in colour may occur between batches, Dimensions are nominal.						

Visit www.armstrongflooring.com.au or contact

Customer Service 1800 632 624 for technical data, installation, cleaning, maintenance instructions and samples or

Email: customer_services@armstrongflooring.com

TIMBERLINE PLUS TRANSLATIONS PLUS HETEROGENEOUS VINYL SHEET



ACADIAN OAK – WELL VERSED PLUS
4X373740



ACADIAN OAK – OILED PLANK PLUS
4X373720



BLANC PLUS
4X032400



CALDE PLUS
4X031300



LUCI PLUS
4X031600



MAHOGANY – CACAO PLUS
4X373700



OAK – BONA FIDE PLUS
4X373600



OAK – LIKE A ROCK PLUS
4X373590



OAK – SOLID PLUS
4X373570



OAK – TOO RIGHT PLUS
4X041400



OBRA PLUS
4X062200



RUSTIC BEECH – COWABUNGA PLUS
4X373490



RUSTIC BEECH – HANG TEN PLUS
4X373480



RUSTIC BEECH – LIFE IS A PLUS
4X373470



SOLLU PLUS
4X061100



LITHOS STONE – ANDESITE PLUS
4S3433003