

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



DESCRIPTION

The RGBW data repeater is required for runs of RGB or RGBW lighting that exceed the wattage of the initial driver capacity. An additional driver in conjunction with the repeater is required to power extended runs.

Need help with your RGBW LED lighting applications? Our lighting experts are here to help! Contact us today for assistance with lighting plan or installation instructions.

SPECIFICATIONS

Input Voltage: 5V-24V DC

Total Output of Current: Max 4 x 8A

Output Channel: 4

Max Wattage: 768 Watts

Working Temperature: -20-60 °C

Required: 12V DC or 24V DC LED Power Supply

Dimensions: 5.79 in. L x 2.76 in. W x 1.34 in. H

147 mm L x 70 mm W x 34 mm H

Warranty: 2 Year Limited

Remarks: Power supply voltage range is 5V-24V DC, it can not be connected to other voltage range. Power wire must not short to each other, in case of short circuit. The outgoing line should connect correctly according to the color in the wiring diagram (included in the product box).

KEY FEATURES

- Easy Installation
- Energy-Efficient Data Signal Repeater
- Rugged Housing
- Low Profile Design
- CE, ROHS Listed

APPLICATIONS

- Trade Show & Exhibit Lighting
- Retail Display Lighting
- Architectural Lighting
- Hotels, Casinos, and Clubs
- Custom Lighting Shows
- Stage Lighting