

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness:	265 Lumens/ft 869.2 Lumens/meter
Power (Watts):	2.4 watt/ft 7.8 watt/meter
Input Voltage:	12V DC
LED CCT:	6000K Cool White 4100K Natural White 3000K Warm White 2700K Extra Warm White Red, Green, Blue, or Amber
CRI:	90+
IP Rating:	IP20
Environment:	Indoor Use - Dry Location
Beam Angle:	120°
LED Density:	18 LEDs/ft 300 LEDs/reel
LED Chip Size:	SMD 2835
LED Spacing:	0.66 in / 16.7 mm
Length:	16.4 ft / 5 meters long
Width:	0.31 in / 8 mm wide
Height:	0.06 in / 1.6 mm thick
Cut Increment:	2 in / 50.8 mm at cut marking
Backing:	3M Adhesive
Manufacturer:	Elumalight
Rating	UL, ETL, RoHS
Avg. Lifetime	± 30,000 - 50,000 hours

DESCRIPTION

LED Standard Tape Lights are made with commercial-grade PCBs to ensure our LED strips lasts longer and runs cooler with high consistency and even illumination. It is perfectly designed for tradeshow decoration, exhibition lighting, retail display lighting, back-lighting applications, and more. The LED Standard Tape Light gives you the freedom to easily design and install lighting for almost any surface or object.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 2835 LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or edge-lighting for sign letters
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

