

# EL-HO4-RGB LED RGB COB Flexible Tape Lights 24V DC

#### JOB NAME: SPECIFICATION SHEET LOCATION: QUOTE/REF#: +DC24V +DC24V +DC24V +DC24V DC24V +0C24 -R -R -R DC24V +DC24 BGR 8GR .... 88 s. -6 ... 88 c 88 s' -G 8 8 G 88 s' -0 .... .... 88 B' -

# SPECIFICATIONS

Brightness:	98(R)/285(G)/24(B) lumens/meter
Power (Watts):	5 watt/ft
	15 watt/meter
Input Voltage:	24V DC
LED Color:	RGB (Red, Green, Blue)
IP Rating:	IP20
Environment:	Indoor Use - Dry Location
Beam Angle:	180°
Length:	16.4 ft / 5 meters long
Width:	0.39 in / 10 mm wide
Height:	0.08 in / 2 mm thick
Cut Increment:	1.96 in / 50 mm at cut marking
Backing:	3M Adhesive
Manufacturer:	Elumalight
Rating	UL, ETL, RoHS
Avg. Lifetime	± 30,000 - 50,000 hours
Required:	24V DC LED Driver, LED RGB Controller

# DESCRIPTION

LED 24V DC LED Color Changing RGB COB Flexible Tape Lights are ideal for displays, exhibitions, under-cabinet, cove lighting applications. It gives you the freedom to easily design and install colorful continuous lighting for almost any surface or object with even lighting illumination and no hot spots. The RGB COB LED Tape Light is made with wire leads on the ends of each 16.4 ft reel and can be cut every 1.96 inches (50 mm) at its cut marking points.

# **KEY FEATURES**

- Continuous lighting without any hotspots
- Fully Dimmable
- Flexible and Durable LED RGB COB Tape
- 6 in. lead length on each end
- Conductor lead colors: Black (24 V+), Red (Red), Green (Green), Blue (Blue)
- Low Profile design
- Maintenance-free

# APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

