

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

- Brightness:** 500 Lumens/ft
1640 Lumens/meter
- Power (Watts):** 4.4 watt/ft
14.4 watt/meter
- Input Voltage:** 24V DC
- LED CCT:** 2700K, 3000K, 4000K, 6000K options
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 180°
- Length:** 16.4 ft or 100 ft
- Width:** 0.31 in / 8 mm wide
- Height:** 0.06 in / 1.6 mm thick
- Cut Increment:** 1.77 in / 45 mm at cut marking
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** 24V DC LED Driver

DESCRIPTION

LED 24V COB Flexible Tape Lights are ideal for displays, exhibitions, under-cabinet, cove lighting applications. It gives you the freedom to easily design and install lighting for almost any surface or objects with even lighting illumination and no hot spots. This LED COB Flexible tape light is energy efficient with uniform illumination output. You can utilize our 10mm wide LED tape light joiners and power feeds for a solder-free install.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- LED Chips are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

Cuttable every 1.77 in.
(45mm)
at the cut mark

