

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

- Brightness:** 14.25 in. - 1200 Lumens
18.5 in. - 1800 Lumens
- Power (Watts):** 14.25 in. - 12 Watt
18.5 in. - 18 Watt
- Input Voltage:** 24V DC
- LED CCT:** 14.25 in. - 6000K Cool White
14.25 in. - 3000K Warm White
18.5 in. - 6000K Cool White
18.5 in. - Blue
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 60°
- Lengths:** 14.25 in or 18.5 in long
- Module Width:** 1 in / 25.4 mm wide
- Module Height:** 0.5 in / 12.7 mm thick
- Mounting:** Screw through pre-drilled holes on each module, screws not included
- Accessories:** **EL-LUM-PF** 12 in Power Feed
EL-LUM-JMP 20 in M/F Jumper
- Manufacturer:** Elumalight
- Rating:** UL Listed
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Warranty:** 3 years limited
- Remarks** *Not to exceed 80% of LED Driver Capacity. Not recommended to be surface mounted directly onto wooden surfaces.
- * Required:** Requires **24V DC LED Power Supply** and **LED LumaStrip Power Feed**. Sold Separately

DESCRIPTION

24V DC LED LumaStrip Lights are designed to provide the superior-quality lighting outputs. They are great for large retail displays and graphic lightboxes. We have designed the LED LumaStrip Light Modules that give you the best performance and versatility.

LED LumaStrip Lights are energy efficient, frameless, and low profile. Each LumaStrip Lights can be linked together with supplied connectors for continuous run. By simply placing these fixtures on the interior of any extrusion, LumaStrip will effectively showcase your graphic or product evenly illuminating the entire display.

Each of LED LumaStrip Light Modules utilizes a diffuser lens around the LED chipset to distribute lights evenly at a beam angle up to 60°. This allows it to illuminate shallow light boxes with virtually no hot spots. Available in 14.25 inches or 18.5 inches length options.

KEY FEATURES

- No hotspots & uniform illumination
- Maintenance-free & Cost-effective light source
- LED Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Easy Installation
- Up to 50,000 hours Lifespan

APPLICATIONS

- Retail Display
- SEG Graphic Display Light Boxes
- Back-lit Graphics
- Custom DIY projects



SOLD SEPARATELY



SKU: EL-LUM-PF
LED LumaStrip Power Feed
12 in



SKU: EL-LUM-JMP
LED LumaStrip
Jumper 20 in



SKU: EL-PNP-xxW-24V
24V DC LED Pre-Wired
Constant Voltage Drivers