

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness:	1700 Lumens - (24 in.) 2600 Lumens - (40 in.)
Power:	30 Watts - (24 in.) 54 watts - (40 in.)
Input Voltage:	100-240V AC
LED CCT:	5000K
CRI:	90+
Diffuser:	Clear Glass
IP Rating:	IP65
Environment:	Wet or Dry Locations
Dimensions:	24 in L x 2.75 in W x 2.625 in H or 4.875" H (with Bracket) EL-LWW-50K-24-IP65 40 in L x 2.75 in W x 2.625 in H or 4.875" H (with Bracket) EL-LWW-50K-40-IP65
Mounting:	Surface Mount with Included Bracket
Manufacturer:	Elumalight
Rating:	UL, ETL
Avg. Lifetime:	± 50,000 hours
Warranty:	3 Year Limited

DESCRIPTION

Elumalight High Output linear LED wall washer lights are perfect for applications where a large amount of intense lighting is required. These LED Wall Wash fixtures are slim and can be easily concealed.

These LED wall wash fixtures are the ultimate choice to exhibit designers, electricians, and architects for its high-performance lighting output with a throwing distance of 30+ ft.

KEY FEATURES

- Easy Installation
- Adjustable mounting bracket allows adjustment after fixed mounting
- Maintenance-free
- Solid-state construction makes for high vibration and shock resistance
- LEDs Chipsets are super bright, high intensity and energy efficient
- Extremely long life: up to 50,000 hours operation
- No RF interference
- Suitable for Indoor or Outdoor Environment - Waterproof IP65
- UL & ETL Listed, RoHS, CE

APPLICATIONS

- Trade Show and Exhibition Displays
- Retail Displays
- Architectural lighting for canopies, corridors, archways, windows
- Downlighting or uplighting for wall wash applications
- Commercial & Residential Landscape lighting
- Excellent for hospitality applications such as bars, restaurants, clubs, hotels
- Road and bridge lighting
- Statue and sculpture lighting illumination

