


SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____


QUOTE/REF#: _____



SPECIFICATIONS

Brightness:	500 Lumens/ft
Power:	3.6 watt/ft
Input Voltage:	12V DC
LED CCT:	6000K Cool White or 3000K Warm White
CRI:	90+
IP Rating:	IP20
Environment:	Indoor Use - Dry Location
Beam Angle:	120°
Length:	6, 12, 18, 24, 36, 43, 55, or 67 in. options
Width:	0.62 in / 15.7 mm wide
Height:	0.50 in / 12.7 mm thick
Mounting:	Each LED Titan Light Bar includes 2 pcs metal mounting clips
Manufacturer:	Elumalight
Rating:	UL, ETL, RoHS
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	3 years limited

Length	Watts	Lumens
12"	3.6	500
18"	5.4	750
24"	7.2	1000
36"	10.8	1500
43"	12.9	1792
55"	16.5	2292
67"	20	2792



DESCRIPTION

LED High Output Titan Light Bars are ideal for displays, exhibitions, under-cabinet, cove lighting applications. It gives you the freedom to easily design and install lighting for almost any surface or objects with even lighting illumination and no hot spots.

This LED High Output Titan Light Bar is energy efficient with uniform illumination output. The sleek design allows this unit to be concealed in spaces, it can also rotate with supplied mounting clips to easily achieve desired light beam direction.

You can utilize our LED Titan Light Bar power feeds and accessories for easy plug-n-play install. Available to order in 3000k or 6000k color temperatures. Sold in various length options.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- LED Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

SOLD SEPARATELY



<i>Order SKUs</i>	<i>Product Name</i>
EL-N-MMC	STANDARD MOUNTING CLIP
EL-N-MAGC	MAGNETIC MOUNTING CLIP
EL-N-LENS-xx	ACRYLIC WHITE FROST LENS
* Available in 12", 18", 24", 36", 43", 55", or 67" Lengths (Ordering SKU Example: EL-N-LENS-12)	
EL-N-DPF-8	8" M/F DIRECT POWER FEED
EL-N-DPF-16	16" M/F DIRECT POWER FEED
EL-N-DPF-36	36" M/F DIRECT POWER FEED
EL-N-HWPF-72	72" HARD WIRE POWER FEED
EL-N-AWPF-36	36" ANGLE H.W. POWER FEED
EL-N-JMP-8	8" M/M JUMPER CORD
EL-N-JMP-12	12" M/M JUMPER CORD
EL-N-JMP-36	36" M/M JUMPER CORD
EL-N-YC-2	2-WAY M/F POWER FEED
EL-N-YC-3	3-WAY M/F POWER FEED
EL-N-YC-5	5-WAY M/F POWER FEED
EL-N-DJ	DIRECT JOINER
EL-N-AJ	90° ANGLE JOINER
EL-N-ILSW	IN-LINE ON/OFF SWITCH