

EL-STP LED Step Lights

SPECIFICATION SHEET





SPECIFICATIONS

Brightness: 37 Lumens Power: 1.5 watts

Input Voltage: 120V, 120-277V AC, or 12V DC

LED CCT: 3000K Warm White

CRI:

Yes, except non-dimmable modules Dimmable:

Environment: IP65 - Wet Locations

Beam Angles: 110°

Dimensions: 4.75 in L x 2.31 in W x 0.375 in D


Mounting: LED Step Light can be recess mounted to


2" x 4" standard junction box using mounting screws provided.

Finish: White Manufacturer: Elumalight Rating: **UL Listed**

Avg. Lifetime: ± 30,000 - 50,000 hours

Warranty: 5 Year Limited





JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

Elumalight LED Step Light Modules are energy efficient and provide maintenance-free illumination with a long lifespan. They are IP65 rated suitable for indoor or outdoor environments. Each LED Step Light comes with a 2 in. x 4 in. gasket for exterior applications.

It is a recessed LED light fixture that is an excellent retrofit for the staircase, stairway, and pathway lighting. The small size makes it versatile enough for infinite applications.

Each step light is selected with your choice of LED Step Light Faceplates (sold separately) with various styles and finishes to complete the lighting installation.

The LED Step Light Modules are made with high impact, weather-resistant polycarbonate casing. Its compact size with universal driver for easy installation and wiring into USA standard 2 in. x 4 in. junction boxes using mounting screws provided. No rough-in box required to install the LED Step Lights.

KEY FEATURES

- Low profile design, flush to wall aesthetics
- Energy-efficient LED chipsets
- Rated IP65 for indoor or Outdoor applications
- Easy to install and wire to USA standard 2x4 junction
- Connect sets of LED step lights to a branch circuit and use a wall switch for On/Off control
- The LED Step Light Module is only compatible with Step 1 Dezigns Faceplates
- C/US UL Listed

APPLICATIONS

- Walls
- Staircase
- **Stairways**
- **Pathways**

ORDER SKUS

Product SKU	Dimming	Input Voltage
EL-STP-32K-12V	Dimmable	12V DC
EL-STP-32K-120	Dimmable	120V AC
EL-STP-32K-UNVD	Non-Dimmable	120-277V AC















Standard Style Faceplate Options



SSM Smooth Lens



SVL Vertical Louver



SVS Vertical Scoop



SHL Horizontal Louver



SHS Horizontal Scoop



FPF Faceplate Frame

Designer Style Faceplate Options



DVW Vertical Wave



DVL Vertical Louver



DHW Horizontal Wave



DHL Horizontal Louver

ORDERING GUIDE:

Example: EL-STP-SSM-WH

SERIES	FACEPLATE TYPE	FINISH
EL-STP	See Above Options to Select Standard or Designer Style Faceplates	WH - White DB - Bronze SS - Stainless