

SPECIFICATION SHEET

EL-SWV LED Swivel Downlight 7 Watt

QUOTE/REF#:

JOB NAME: LOCATION:









SPECIFICATIONS

Brightness: 700 Lumens **Power (Watts):** 7 Watt **Input Voltage:** 500 mA

LED CCT: 3000K or 5000K

IP Rating: IP20

Environment: Indoor Use - Dry Location

Beam Angle: 40 - 60° **LED Density:** 1 LEDs

Cut-out: 2.75 in / 69.85 mm Diameter

Diameter: 3.25 in / 82.55 mm **Gimbal Depth:** 1.75 in / 44.45 mm

Finish: Black, White, Satin Nickel, Bronze

Manufacturer: Elumalight Rating: UL, ETL Listed

Avg. Lifetime: ± 30,000 - 50,000 hours

Required: 500mA driver. Sold Separately.

Hardwire connection is required if connecting more than 1 fixture.

DESCRIPTION

The 7 Watt LED Swivel Downlight is one of our most powerful and efficient recessed fixtures. It is a fully recessed LED light that adds brightness, focused illumination to any space. Equivalent to a 75 Watt MR16 Halogen light without the heat and UV effects.

The EL-SWV-DPC fits into walls, ceilings, cabinetry, under countertops, bars, display cases, home entertainment centers, and retail window displays. The LED Swivel fixture is made of cast aluminum and features an adjustable gimbal design for directed lighting with 38° swivels.

The LED recessed gimbal light can fit into tight spaces for easy installation. It is adjustable as a spotlight and can swivel to the beam directions desired. Available in 3000K Warm White or 5000K Cool White LED CCT options.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- No IR or UV radiation
- Suitable for flat ceiling or under-cabinet installations
- Easy to mounting and install with tension spring clamps
- LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Long lifespan: Up to 50,000 hours

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways,
- Downlighting or Uplighting Recessed Applications
- Under-cabinet, Under-Counter, or accent lighting









