

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



DESCRIPTION

LED CCT Selectable T5 Integrated Linear Lighting is an ideal solution for multiple environments such as coves and soffits, retail displays, undershelf, undercabinet, and step lighting.

Easily select the LED color temperatures from 3000K, 4000K, to 5000K by pushing the built-in switch. The LED Micro T5 Integrated Lights are designed to perform efficiently in conditions where fluorescent, halogen, and low voltage luminaires have traditionally been used.

Available in 24 inches, 36 inches, or 48 inches length options with mounting hardware and hardwire power feed included. The EL-T5-6PC 6 Ft length 3-Prong AC power cord with the Plug option is sold separately.

SPECIFICATIONS

- Input Voltage:** 100-277V AC
- LED CCT:** Selectable 3000K - 4000K - 5000K
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 130°
- Lengths:** 24 in, 36 in, or 48 in options
- Width:** 1.02 in / 26 mm wide
- Height:** 1.38 in / 35 mm thick
- Mounting:** Surface Metal Mounting Clips
- Included:**
 - 2 x Spring Steel Clips
 - 2 x Mounting Screws
 - 2 x Plastic Anchors
 - 1 x End Connector
 - 1 x Spliced Wire Power Feed
 - 1 x 6 in. Jumper
- Manufacturer:** Elumalight
- Lifespan:** ± 30,000 - 50,000 hours
- Rating:** UL, ETL, RoHS

KEY FEATURES

- Patent Male-female linkable design
- Seamless & No Dark in-line connection
- UL ETL TUV SAA approved, DLC Listed
- Aluminum housing for excellent heat dissipation
- Heat protection system, with excellent internal driver
- Enjoy Hassle-free, safe and easy Installation

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Replaces fluorescent NCF fittings

Length	Watts	Lumens
24"	7	770
36"	12	1320
48"	15	1650

