


C3037W-3 Exp C series multicoupler, 7" cavities, 3 pass 1 reject, Takrak or wall mount, 430-450 MHz

- Three bandpass cavities and one reject cavity
- Combines transmitters or receivers with inter-channel spacing down to 1 MHz
- High selectivity ideally suited for applications where significant expansion is contemplated
- Takrak or wall mount

Sinclair's C-Series multicouplers offers excellent performance combined with ease of expandability required in many multicoupling systems. Each C-Series multicoupler channel consists of a reject cavity and one or more bandpass cavities, depending on the selectivity required. The reject cavity acts as a switch, diverting the wanted channel frequency to or from the antenna, while allowing the remaining channel frequencies to flow in the antenna feed-thru line to or from the remaining C-Series multicoupler channels.

Because cable lengths between C-Series multicoupler channels are not critical, additional channels may be easily added in the field. However, in order to minimize losses due to cabling, these interconnecting cables should be as short as possible. These highly versatile combiners offer improved performance through the addition of single or dual stage isolators and/or one or more Q-circuit cavities wherever they are required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications

Frequency Range	MHz	430 to 450	
Output Connectors		N-Female	
Input VSWR (max)		1.5:1	
Insertion loss (min)	dB	1.7	
Insertion Loss (max) Tx to Ant	dB	3.2	
Average Power Input (max)	W	185-300	*1
Frequency separation (min)	MHz	1	
Thru Line Average Power (max)	W	300	

Notes


*1 : 300W @ 1.7DB/ 185W @ 3.2DB

Mechanical Specifications

Width	in (mm)	32 (813)
Depth	in (mm)	8 (203)
Length/ Height	in (mm)	16 (406)
Net Weight	lbs (kg)	32 (14.53)
Actual shipping weight	lbs (kg)	45 (20.43)
Shipping dimensions	in (mm)	32x9x42 (813x229x1067)

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
-------------------	---------	--------------------------



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com