


Transmitter Combiners UHF and Tetra Transmitter Combiners CTx450F-R-y Series

CT2450F-R-5 Cavity-ferrite combiner, 2 channel, High 'Q' 10" 1/4 wave cavities, 459-512 MHz

- · Broad bandwidth over the specified band
- Dual stage isolators and 10 inch high 'Q' 1/4 wave bandpass cavity for each channel
- · Works for inter-channel spacings as close as 100 KHz

The CTx-450F-R-y series combines the mechanical features of open-frame construction with UHF cavities to provide a high performance transmitter combiner for the 406-512 MHz frequency band. Typical insertion losses for 4 and 6 channels are illustrated below.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Copyright © Sinclair Technologies

Environmental Specifications

Temperature range




Transmitter Combiners UHF and Tetra Transmitter Combiners CTx450F-R-y Series

A Norsat Company Norsat

Electrical Specifications			
Frequency Range	MHz	459 to 512	
Input VSWR (max)		1.25:1	
Maximum Input Power (per channel)	W	150	
Input Connectors		N-Female	
Output Connectors		N-Female	
Frequency separation (max)	MHz	12	
Frequency separation (min)	MHz	0.1	
Insertion Loss (max) Tx to Ant	dB	3.5	
Isolation Tx to Tx	dB	60	
Isolation antenna to Tx	dB	50	
Output VSWR		2:1	
Number of channels		2	
Mechanical Specifications Width	in (mm)	21 (533)	
Depth	in (mm)	21 (533)	
Length/ Height	in (mm)	38 (965)	
Length/ Height Finish	in (mm)	38 (965) chemical conversion	
<u> </u>	in (mm)	,	
Finish	,	chemical conversion	

°F (°C)

Ordering InformationSpecify frequency for the two Tx channels.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018639		CT2450F-R-5	Issue: 3	Dated: 06-04-16 Dated: 27-04-15

-22 to +140 (-30 to +60)