

Transmitter Combiners
UHF and Tetra Transmitter Combiners
CTx450F-R-y Series

CT3450F-R-3 Cavity-ferrite combiner, 3 channel, High 'Q' 10" 1/4 wave cavities, 406 to 440 MHz

- · Broad bandwidth over the specified band
- Dual stage isolators and 10 inch high 'Q' 1/4 wave bandpass cavity for each channel
- · Works for inter-channel spacings as close as 100 KHz

The CTx-450F-R-y series combines the mechanical features of open-frame construction with UHF cavities to provide a high performance transmitter combiner for the 406-512 MHz frequency band. Typical insertion losses for 4 and 6 channels are illustrated below.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		CT3450F-R-3	Issue: 3	Dated: 30-04-15

Copyright © Sinclair Technologies

Product Specification Sheet EPR 018640 Customer Tech Manual 006277

Dated: 27-04-15

Temperature range




Transmitter Combiners UHF and Tetra Transmitter Combiners CTx450F-R-y Series

A Norsat Company in Norsat

Frequency Range	MHz	406 to 440
Input VSWR (max)		1.25:1
Maximum Input Power (per channel)	W	150
Input Connectors		N-Female
Output Connectors		N-Female
Frequency separation (max)	MHz	12
Frequency separation (min)	MHz	0.1
Insertion loss (max) Tx to Ant	dB	4.2
Isolation Tx to Tx	dB	60
		_
Isolation antenna to Tx	dB	50
Isolation antenna to Tx Output VSWR	dB	50 2:1
	dB	
Output VSWR	dB in (mm)	2:1
Output VSWR Number of channels Mechanical Specifications		2:1 3
Output VSWR Number of channels Mechanical Specifications Depth	in (mm)	2:1 3 21 (533)
Output VSWR Number of channels Mechanical Specifications Depth Length/ Height Width Weight	in (mm) in (mm)	2:1 3 21 (533) 38 (965)
Output VSWR Number of channels Mechanical Specifications Depth Length/ Height Width	in (mm) in (mm) in (mm)	2:1 3 21 (533) 38 (965) 21 (533)
Output VSWR Number of channels Mechanical Specifications Depth Length/ Height Width Weight	in (mm) in (mm) in (mm)	2:1 3 21 (533) 38 (965) 21 (533) 75 (34.05)

°F (°C)

Ordering Information Specify frequency for the three Tx channels.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018640		CT3450F-R-3	Issue: 3	Dated: 30-04-15 Dated: 27-04-15

-22 to +140 (-30 to +60)