

Transmitter Combiners
UHF and Tetra Transmitter Combiners
CTx450F-R-y Series

CT3450F-R-4 Cavity-ferrite combiner, 3 channel, High 'Q' 10" 1/4 wave cavities, 430 to 470 MHz

- · Broad band isolators covering the specified band
- Dual stage isolators and 10 inch high 'Q' 1/4 wave bandpass cavity for each channel
- · Works for inter-channel spacings as close as 100 KHz

The CTx-450F-R-y series combines the mechanical features of open-frame construction with UHF cavities to provide a high performance transmitter combiner for the 406-512 MHz frequency band. Typical insertion losses for 4 and 6 channels are illustrated below.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
B 1 10 'f 1'	01 1	OT04505 D 4		D 1 1 00 04 45

Page 1/2

Temperature range




Transmitter Combiners UHF and Tetra Transmitter Combiners CTx450F-R-y Series

A Norsat Company in Norsat

Frequency Range Input VSWR (max) Input Power (per channel) Input Connectors	W	1.25:1 150	
	W	150	
nput Connectors		100	
		N-Female	
Output Connectors		N-Female	
requency separation (max)	MHz	12	
requency separation (min)	MHz	0.1	
nsertion loss (max) Tx to Ant	dB	4.2	
solation Tx to Tx	dB	60	
solation antenna to Tx	dB	50	
Output VSWR		2:1	
Number of channels		3	
Mechanical Specifications Depth	in (mm)	21 (533)	
.ength/ Height Vidth	in (mm)	38 (965)	
	in (mm)	21 (533)	
Veight Finish	lbs (kg)	75 (34.05) chemical conversion	
	lhs (ka)		
	(0)	, ,	
Actual Shipping weight Shipping dimensions	lbs (kg) in (mm)	80 (36.32) 22x22x43 (559x559x1092)	

°F (°C)

Ordering Information Specify frequency for the three Tx channels.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018640		CT3450F-R-4	Issue: 3	Dated: 30-04-15 Dated: 27-04-15

-22 to +140 (-30 to +60)