

FP20402N-1-2.0 Preselector, 2 MHz B.W., High Performance, 130-150 MHz

- Extremely high selectivity, high performance design
- Very compact, low profile VHF preselector for 130-150 MHz
- Easy to tune with very high temperature stability
- Mounted on 19" rack mountable plates

The FP20402N preselectors covers the 130-150 MHz band and 150-170 MHz band. Each preselector is offered with one of two band widths - 1.0 MHz and 2MHz. It weighs 9 pounds / 4.1 Kg with height of 3.5 in / 89 mm, width of 19 in / 483 mm (19" rack mountable), and depth of 17 in / 432 mm. The FP20402N is easy to tune, offers very high temperature stability, provides extremely high selectivity, and low insertion loss, typically less than 1.6 dB operating at Fo.



Application Notes

- Attenuation of 48dB @ fo minus 5 MHz and 60dB @ fo plus 5 MHz

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications

Frequency Range	MHz	130 to 150
Input VSWR (max)		1.5:1
Approx Bandwidth @ 50 dB	MHz	9.5
Bandwidth at specified insertion loss	MHz	2
Insertion loss (typ)	dB	1.6
Impedance	Ω	50
Input Connectors		N-Female
Output Connectors		N-Female

Mechanical Specifications

Width	in (mm)	19 (483)
Depth	in (mm)	17 (432)
Length/ Height	in (mm)	3.5 (89)
Weight	lbs (kg)	9 (4.09)
Estimated Shipping Weight	lbs (kg)	16 (7.26)
Shipping dimensions	in (mm)	25x19x7 (635x483x178)
Mounting configurations		19 inch rack

Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com