

FP20402N-2-1.0 Preselector, 1 MHz B.W., High Performance, 150-174 MHz

- Extremely high selectivity, high performance design
- Very compact, low profile VHF preselector for 150-174 MHz
- Easy to tune with very high temperature stability
- Mounted on 19" rack mountable plates

The FP20402N preselectors covers the 130-150 MHz band and 150-174 MHz band. Each preselector is offered with one of two band widths - 1.0 MHz and 2MHz. It weighs 9 pounds / 4.1 Kg with height of 3.5 in / 89 mm, width of 19 in / 483 mm (19" rack mountable), and depth of 17 in / 432 mm. The 1 MHz bandwidth FP20402N is easy to tune, offers very high temperature stability, provides extremely high selectivity, and low insertion loss, typically less than 2.0 dB operating at Fo.



Application Notes

- Attenuation of 55dB @ fo minus 5 MHz and 65dB @ fo plus 5 MHz

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications

Frequency Range	MHz	150 to 174
Input VSWR (max)		1.5:1
Approx Bandwidth @ 50 dB	MHz	7.5
Bandwidth at specified insertion loss	MHz	1
Insertion loss (typ)	dB	2
Impedance	Ω	50
Input Connectors		N-Female
Output Connectors		N-Female

Mechanical Specifications

Width	in (mm)	19 (483)
Depth	in (mm)	17 (432)
Length/ Height	in (mm)	3.5 (89)
Weight	lbs (kg)	9 (4.09)
Estimated Shipping Weight	lbs (kg)	16 (7.26)
Shipping dimensions	in (mm)	25x19x7 (635x483x178)
Mounting configurations		19 inch rack

Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com