

Preselector Filters
UHF and Tetra Preselectors
FP30401 Series

FP30401T-2-3

Preselector, 3 MHz bandwidth, compact, TNC connectors, 440-480 MHz

Also referred as: FP30401T*2-3

- · Suitable for most standard multicoupling requirements
- Can be mounted directly on 1.75 " high receiver multicoupler tray
- Rugged compact construction with TNC-type female connectors

The FP30401 series preselectors are compact units that are suitable for most standard multicoupling requirements. Their size permits them to be mounted directly on the 1 3/4 in (44.5 mm) high receiver multicoupler trays.



BNC connector model shown.


Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Deadust Consideration Chart		EDOMANT O O	January 11	Datady 26 04 16



Preselector Filters
UHF and Tetra Preselectors
FP30401 Series

A Norsat Company Norsat International Inc.

Frequency Range	MHz	440 to 480
Input VSWR (max)		1.5:1
Insertion loss (typ)	dB	2
Bandwidth at specified insertion loss	MHz	3
Impedance	Ω	50
Average Power Input (max)	W	20
Input Connectors		TNC-Female
Output Connectors		TNC-Female
Approx Bandwidth @ 50 dB	MHz	25
Mechanical Specifications		
	in (mm)	4.2 (107)
Width	in (mm) in (mm)	4.2 (107) 7.5 (191)
Width Depth	in (mm) in (mm) in (mm)	4.2 (107) 7.5 (191) 1.3 (33)
Width Depth Length/ Height	in (mm)	7.5 (191)
Width Depth Length/ Height Weight	in (mm) in (mm)	7.5 (191) 1.3 (33)
Width Depth Length/ Height Weight Actual shipping weight	in (mm) in (mm) lbs (kg)	7.5 (191) 1.3 (33) 1.5 (0.68)
Width Depth Length/ Height Weight Actual shipping weight	in (mm) in (mm) lbs (kg) lbs (kg)	7.5 (191) 1.3 (33) 1.5 (0.68) 2 (0.91)
Mechanical Specifications Width Depth Length/ Height Weight Actual shipping weight Shipping dimensions Environmental Specifications	in (mm) in (mm) lbs (kg) lbs (kg)	7.5 (191) 1.3 (33) 1.5 (0.68) 2 (0.91)



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		FP30401T-2-3	Issue: 11	Dated: 26-04-16

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies