

FP40718CLNHP-5-12 Combine preselector, 12 MHz B.W., N-female connector, H.P., 763-775 MHz

- Covers the entire 763-775 MHz frequency range
- 1.0 dB insertion loss over the pass band
- 80 dB attenuation at 793 MHz
- 300 Watt power handling

www.sincltech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sincltech.com	salesuk@sincltech.com	salesla@sincltech.com	salescan@sincltech.com

Product Specification Sheet  
EPR 018320

FP40718CLNHP-5-12

Issue: 12

Dated: 08-10-13  
Dated: 01-05-08

#### Electrical Specifications

Frequency Range	MHz	763 to 775
Pass band Insertion Loss (max)	dB	1.0
Input VSWR (max)		1.5:1
Impedance	Ω	50
Number of Cavities		7
Average Power Input (max)	W	300
Input Connectors		N-Female
Output Connectors		N-Female
Bandwidth at specified insertion loss	MHz	12
Attenuation at 793 MHz	dB	80

#### Mechanical Specifications

Depth	in (mm)	6.68 (170)
Length/ Height	in (mm)	1.75 (44)
Width	in (mm)	19 (483)
Weight	lbs (kg)	10 (4.54)
Mounting configurations		19 inch rack

#### Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com